



AT A GLANCE

- Real 600W RMS with accurate deep tones
- CELTO woofer with trimmed chassis for ultra compact format
- Birch plywood cabinet with smooth texture or varnish finish
- High Efficiency for incredible SPL to Size ratio
- 6 M8 Flying points for added versatility
- Available in Black, White, Natural and Oak colors

SPECIFICATIONS

Power handling (AES Standard)	600W RMS / 2400W Peak
Nominal impedance	8 Ohm
Frequency response (-6dB half space, no EQ)	42~1500Hz
Manufacturing Consistency tolerance	±2dB from 50 to 400Hz
Average Sensitivity (wideband 200~16000Hz)	97dB/W/m
Calculated Maximum SPL / 1m	125dB continuous / 131dB Peak
Nominal Directivity (-6dB)	omnidirectional in usage range
Recommended low cut filter	35Hz 24dB/oct
Low Frequency driver	Custom 13.5" CELTO Acoustique Ferrite magnet, 3.6" Voice Coil
Crossover	No. Must use external DSP or dedicated iFIX amplifiers
Flying hardware	6 M8 points
Connectors	Screw terminals with banana plug
Cabinet	CNC made with tongue and groove assembly 18 mm birch plywood
Finish	Smooth textured coating (Black and White colors) or Varnish finish (Natural and Oak colors)
Size (HxWxD)	415x545x500mm
Weight	25kg net / 30kg gross