eurolite®

EUROLITE Set EUROLITE Wind Up DJ Heavy Bundle IV



The article is no longer in our assortment.

Features:

EUROLITE STT-400/85 Winch Stand TÜV/GS

High-quality winch-stand, maximum load 85 kg, maximum height 400 cm

- 1-gear winch for easy lifting of the loads
- Automatic braking system
- Safety bolt for mechanical locking
- Easy handling
- Complies with DIN 15560-27 and DIN EN ISO 12100-2
- Adjustable height
- TÜV Süd certified
- For application areas such as: Mobile use Package contents
- 1 x user manual

EUROLITE TAH-35M Truss Adapter, large

Adapter from 12 - 35 cm, maximum load WLL 300 kg

- Truss adapter for truss systems up to 55 mm diameter
- Adjustable clamps
- Adjustment between 120 mm and 350 mm
- LGA tested

Package contents

- 1 x adapter, 2 x bolt, 1 x user manual

ALUTRUSS QUADLOCK 6082-2000 4-way Cross Beam

4-point truss system







Logistic

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

- Strong EN-AW 6082 alloy for high loads
- High-quality aluminum-tubes with 50 mm in diameter
- Low weight
- Distance center center: 240 mm
- Easy installation
- Trusspipe: 50 mm
- TÜV Süd certified
- For application areas such as: Theater; Trade fair and shop fitting; clubs/dancing school
- For further information about this product, please refer to the Data Sheet under "Downloads" Package contents
- 1 x connection set

Technical specifications:

Weight:	85,40 kg

EUROLITE STT-400/85 Winch Stand TÜV/GS

Maximum carrying capacity:	85 kg
Minimum load:	25 kg
Standard:	DIN 15560-27, DIN EN ISO 12100-2
Height:	Maximum: 400 cm above 3 sections Minimum: 175 cm
Attachment system:	Ø 35mm
Steel rope:	Ø 4 mm
Type (general stands):	Light stand/wind up
Transport dimensions:	175 cm x 30 cm x 27 cm
Base area:	Ø 160 cm
Weight:	24,10 kg

EUROLITE TAH-35M Truss Adapter, large

Maximum load BGV C1 (8-fold):	150 kg
Maximum load WLL (4-fold):	300 kg
Attachment system:	Ø 35mm
Type (general stands):	Accessory
Material:	Steel
Width:	Maximum: 35 cm
	Minimum: 12 cm
Dimensions:	Width: 46 cm
	Depth: 7,50 cm
	Height: 22,50 cm
Weight:	2,40 kg

ALUTRUSS QUADLOCK 6082-2000 4-way Cross Beam

Setup:

Easy installation

Trusspipe:	50 mm x 2 mm
Welding technique:	TIG-welding
Welding material:	AIMg 5
Alloy:	AIMgSi1 T6
Color:	Alu colored
Strut diameter x thickness:	16 x 2mm
Dimensions:	Length: 200 cm
	Width: 29 cm
	Height: 29 cm
Weight:	10,80 kg