

# **EUROLITE Set EUROLITE Wind Up DJ Heavy Bundle IV**

Art. No.: 09000014

GTIN:









# The article is no longer in our assortment.

Features: Logistic

#### **EUROLITE STT-400/85 Winch Stand TÜV/GS**

High-quality winch-stand, maximum load 85 kg, maximum height 400 cm

- 1-gear winch for easy lifting of the loads
- Automatic braking system
- Safety bolt for mechanical locking
- Easy handling
- Complies with DIN 15560-27 and DIN EN ISO 12100-2
- Adjustable height
- TÜV Süd certified
- For application areas such as: Mobile use

#### Package contents

- 1 x user manual

## **EUROLITE TAH-35M Truss Adapter, large**

Adapter from 12 - 35 cm, maximum load WLL 300 kg

- Truss adapter for truss systems up to 55 mm diameter
- Adjustable clamps
- Adjustment between 120 mm and 350 mm
- LGA tested

#### Package contents

- 1 x adapter, 2 x bolt, 1 x user manual

### ALUTRUSS QUADLOCK 6082-2000 4-Way Cross Beam

4-point truss system

- Strong EN-AW 6082 alloy for high loads
- High-quality aluminum-tubes with 50 mm in diameter
- Low weight
- Distance center center: 240 mm
- Easy installation
- Trusspipe: 50 mm
- TÜV Süd certified
- For application areas such as: Theater; Trade fair and shop fitting; Clubs/dancing school
- For further information about this product, please refer to the Data Sheet under "Downloads"

#### Package contents

- 1 x connection Set

### **Technical specifications:**

Weight: 85,40 kg

### **EUROLITE STT-400/85 Winch Stand TÜV/GS**

Maximum carrying capacity:	85 kg
Minimum load:	25 kg
Standard:	DIN 15560-27, DIN EN ISO 12100-2
Height:	Maximum: 400 cm above 3 sections Minimum: 175 cm
Attachment system:	Ø 35mm
Steel rope:	Ø 4 mm
Type (general stands):	Light stand/wind up
Transport dimensions:	1,75 m x 30 cm x 27 cm
Base area:	Ø 1,6 m
Weight:	24,10 kg
	·

## **EUROLITE TAH-35M Truss Adapter, large**

Maximum load BGV C1 (8-fold):	150 kg
Max. load WLL (4-fold):	300 kg
Width:	Maximum: 35 cm Minimum: 12 cm
Attachment system:	Ø 35mm
Type (general stands):	Accessory
Material:	Steel
Dimensions:	Width: 46 cm Depth: 7,50 cm Height: 22,50 cm
Weight:	2,40 kg

### ALUTRUSS QUADLOCK 6082-2000 4-Way Cross Beam

Setup: Easy installation

Trusspipe:	50 mm x 2 mm	
Welding technique:	TIG-welding	
Welding material:	AIMg 5	
Alloy:	AIMgSi1 T6	
Color:	Alu colored	
Strut diameter x thickness:	16 x 2mm	
Dimensions:	Length: 2 m	
	Width: 29 cm	
	Height: 29 cm	
Weight:	10,80 kg	