



The article is no longer in our assortment.

Features:

EUROLITE LED PAR-56 COB RGB 100W sil

PRO spotlight as DMX model with COB LED

- Equipped with a powerful RGB 100 W COB LED
- Functions: static colors, RGB color mixture, internal programs, dimmer and strobe settings via DMX, Master/Slave
- Dimmer speed (step response) adjustable
- Operable in stand-alone mode or with DMX interface
- Adjustable microphone sensitivity via LCD display
- Comfortable addressing and setting via control panel with LCD display and four operating buttons
- Locking possibility at the mounting bracket
- With color filter frame
- Ready for connection via power cord with safety-plug
- Available in silver or in black
- 1 powerful LED 100 W COB (chip-on-board) 3in1 TCL RGB (homogenous color mix)
- Strobe effect
- Control via DMX; Sound to light via Microphone
- Preprogrammed in EASY SHOW 1; LED PC-Control 512; Light´J; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE
- With a beam angle of 40°
- For further information about this product, please refer to the Data Sheet under "Downloads"

Logistic

ROADINGER Flightcase 4x PAR-56 Spot long

Trunk case, PRO version

- Detachable compartments - case can also be used as universal transport case
- Extra high for transport of spots in short version with mounted hook
- With 4 Device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 1 high-quality butterfly lock
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	20,00 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE LED PAR-56 COB RGB 100W sil

Power supply:	230 V AC, 50 Hz
Power consumption:	130 W
IP classification:	IP20
Power connection:	Fixed power supply cord with safety plug
Lamp type:	LED lamp
LED:	1 x 100 W COB (chip-on-board) 3in1 TCL RGB (homogenous color mix)
DMX channels:	3; 5
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	DMX; Sound to light via Microphone
Preprogrammed in:	EASY SHOW 1; LED PC-Control 512; Light J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE
Beam angle:	40°
Beam angle (1/2 peak):	40°
Housing color:	Silver
Dimensions:	Width: 24 cm Depth: 36,5 cm Height: 31,5 cm
Weight:	2,6 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 4x PAR-56 Spot long

Maximum load:	50 kg
Aluminum profile frames:	30 mm
Case handle:	2 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 1 pc/pcs
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Device compartment:	22 cm x 22 cm x 34 cm
Inside dimensions:	44 cm x 44 cm x 34 cm
Dimensions:	Width: 48,5 cm Depth: 48,5 cm Height: 42,5 cm
Weight:	9,60 kg