



The article is no longer in our assortment.

Features:

ALUTRUSS QUADLOCK 6082-2000 4-Way Cross Beam

4-point truss system

- Strong EN-AW 6082 alloy for high loads
- High-quality aluminum-tubes with 50 mm in diameter
- Low weight
- Distance center - center: 240 mm
- Easy installation
- Trusspipe: 50 mm
- TÜV Süd certified
- For application areas such as: Theater; Trade fair and shop fitting; Clubs/dancing school
- For further information about this product, please refer to the Data Sheet under "Downloads"

Package contents

- 1 x connection Set

Logistic

ALUTRUSS Truss Transport Board Combo incl 3 Wheels

Transport cart with castors for QUADLOCK and TRILOCK truss elements

- The article is delivered dismantled

ALUTRUSS Truss Transport Ridge Combo

Stacking rail for QUADLOCK and TRILOCK truss elements

- Stacking ridge for quick and secure stacking of truss elements on matching transport carts
- Suitable for QUADLOCK and TRILOCK truss elements with 290 mm
- Made in Germany

SHZ Clamping Belt S400 Ratchet 5m/25mm black

Clamping belt

- LC400/800daN surroundings
- Complies with EN 12195-2
- Ratchet lock

Technical specifications:

Weight: 100,38 kg

ALUTRUSS QUADLOCK 6082-2000 4-Way Cross Beam

Setup: Easy installation

Trusspipe: 50 mm x 2 mm

Welding technique: TIG-welding

Welding material: AlMg 5

Alloy: AlMgSi1 T6

Color: Alu colored

Strut diameter x thickness: 16 x 2mm

Dimensions: Length: 2 m
Width: 29 cm
Height: 29 cm

Weight: 10,80 kg

ALUTRUSS Truss Transport Board Combo incl 3 Wheels

Weight: 3,60 kg

ALUTRUSS Truss Transport Ridge Combo

Material: Birch multiplex, 30 mm

Dimensions: Length: 60 cm
Width: 3 cm
Depth: 5 cm

Weight: 500 g

SHZ Clamping Belt S400 Ratchet 5m/25mm black

Standard: EN 12195-2,

Lock: Ratchet lock

Color: Black

Dimensions: Length: 5 m
Width: 2,50 cm

Weight: 300 g
