



Features:

ALUTRUSS TRILOCK 6082-2500 3-way Cross Beam

3-point truss system

- Low weight
- Easy installation
- Trusspipe: 50 mm
- TÜV Süd certified
- For application areas such as: Theater; Trade fair and shop fitting; clubs/dancing school
- For further information about this product, please refer to the Data Sheet under "Downloads"

ALUTRUSS TRILOCK 6082AC-41 4-way Cross

3-point truss system

- Low weight
- Easy installation
- Trusspipe: 50 mm
- Made in Europe
- For application areas such as: Theater; Trade fair and shop fitting; clubs/dancing school

ALUTRUSS TRILOCK 6082AC-25 2-way Corner 90° V

3-point truss system

- Low weight
- Easy installation
- Trusspipe: 50 mm
- Made in Europe

Logistic

- For application areas such as: Theater; Trade fair and shop fitting; clubs/dancing school

ALUTRUSS TRILOCK Base Plate QTG-male

- Trusspipe: 50 mm
- Made in Europe

Technical specifications:

Weight: 106.54 kg

ALUTRUSS TRILOCK 6082-2500 3-way Cross Beam

Setup: Easy installation

Trusspipe: 50 mm x 2 mm

Welding technique: TIG-welding

Welding material: AlMg 5

Color: Alu colored

Strut diameter x thickness: 16 x 2mm

Dimensions: Length: 250 cm
Width: 29 cm
Height: 25.70 cm

Weight: 9.80 kg

ALUTRUSS TRILOCK 6082AC-41 4-way Cross

Setup: Easy installation

Trusspipe: 50 mm x 2 mm

Color: Alu colored

Strut diameter x thickness: 16 x 2mm

Dimensions: Length: 71 cm
Width: 71 cm
Height: 25.70 cm

Weight: 8 kg

ALUTRUSS TRILOCK 6082AC-25 2-way Corner 90° V

Setup: Easy installation

Trusspipe: 50 mm x 2 mm

Color: Alu colored

Strut diameter x thickness: 16 x 2mm

Dimensions: Length: 50 cm
Width: 50 cm
Height: 29 cm

Weight: 4.10 kg

ALUTRUSS TRILOCK Base Plate QTG-male

Trusspipe:	50 mm
Color:	Alu colored
Weight:	0.94 kg

Scope of delivery:

8 x ALUTRUSS TRILOCK 6082-2500 3-way Cross Beam

1 x connection set

1 x ALUTRUSS TRILOCK 6082AC-41 4-way Cross

3 x connection set

4 x ALUTRUSS TRILOCK 6082AC-25 2-way Corner 90° V

1 x connection set