



**The article is no longer in our assortment.**

### Features:

#### ALUTRUSS Steel Base Plate round type A

Baseplate for mobile use (connectors 6082 included)

- For the vertical installation of truss elements
- Multifunctional use
- High durability
- Trusspipe: 50 mm
- Made in Europe
- For application areas such as: Trade fair and shop fitting; Wedding/gala/events

#### ALUTRUSS QUADLOCK 6082-2000 4-Way Cross Beam

4-point truss system

- Strong EN-AW 6082 alloy for high loads
- High-quality aluminum-tubes with 50 mm in diameter
- Low weight
- Distance center - center: 240 mm
- Easy installation
- Trusspipe: 50 mm
- TÜV Süd certified
- For application areas such as: Theater; Trade fair and shop fitting; Clubs/dancing school
- For further information about this product, please refer to the Data Sheet under "Downloads"

#### Package contents

- 1 x connection Set

### Logistic

### ALUTRUSS QUADLOCK End Plate QQGP-Male

- Trusspipe: 50 mm
- Made in Europe
- cone**
- M8 thread

### EUROLITE LCH-36/55M2 Wall mount for monitors

Wall mount

- Wall mount for LCD monitors with a diagonal screen size of 915 mm (36") to 1400 mm (55")
- Adjustable tilting angle
- Stable metal version
- VESA standard
- Mounting materials included in the delivery

### ALUTRUSS QUICK-LOCK Spare Pivot with Pin

QUICK-LOCK set

- Accessories for the robust truss system with Quick-Lock
- For use with TRI/QUAD system
- Trusspipe: 50 mm
- Made in Europe

#### Package contents

- 2 x splint, 2 x bolt

### Technical specifications:

---

#### ALUTRUSS Steel Base Plate round type A

Trusspipe:	50 mm
Material:	Steel
Color:	Alu colored
Dimensions:	Height: 1,60 cm Diameter: Ø 80 cm
Weight:	60 kg

#### ALUTRUSS QUADLOCK 6082-2000 4-Way Cross Beam

Setup:	Easy installation
Trusspipe:	50 mm x 2 mm
Welding technique:	TIG-welding
Welding material:	AlMg 5
Alloy:	AlMgSi1 T6
Color:	Alu colored
Strut diameter x thickness:	16 x 2mm
Dimensions:	Length: 2 m Width: 29 cm Height: 29 cm
Weight:	10,80 kg

**ALUTRUSS QUADLOCK End Plate QQGP-Male**

Trusspipe:	50 mm
Color:	Alu colored
Weight:	1,45 kg
Cone	
Thread:	M8 thread

**EUROLITE LCH-36/55M2 Wall mount for monitors**

Maximum load BGV C1 (8-fold):	30 kg
Max. load WLL (4-fold):	60 kg
Distance to wall:	75 mm
Dimensions:	Width: 49,8 cm Depth: 7,5 cm Height: 70 cm
Weight:	5,30 kg
Interface dimensios:	498 x 700 mm
Distance to wall:	75 mm
Dimensions:	748 x 498 x 75 mm

**EUROLITE TPC-10 Coupler, silver**

Maximum load BGV C1 (8-fold):	75 kg
Max. load WLL (4-fold):	150 kg
Tube diameter sector:	48 - 50 mm
Material:	Aluminum
Color:	Silver
Mounting screw:	M10
Dimensions:	Length: 10 cm Width: 3 cm Depth: 9 cm
Weight:	160 g

**ALUTRUSS QUICK-LOCK Spare Pivot with Pin**

Trusspipe:	50 mm
Color:	Alu colored
Weight:	90 g