



**The article is no longer in our assortment.**

### Features:

#### EUROLITE LED PAR-56 RGB 5mm Short 5CH bk

PAR-56 spot with 151 LEDs in the colors red, green and blue

- Equipped with 151 x 5 mm LED: 51 x red, 49 x green, 51 x blue
- Operable in stand-alone mode or via DMX
- DMX-512 control possible via any commercial DMX-controller (occupies 5 channels)
- 3 or 5 DMX channels selectable for numerous applications
- Sound-control via built-in microphone
- Adjustable microphone sensitivity via LED display
- Comfortable addressing and setting via control panel with LED display and three operating buttons
- Functions: static colors; RGB color blend, internal programs, dimmer and strobe settings via DMX; master/slave
- Housing available in silver or in black
- Locking possibility at the mounting bracket
- Ready for connection with power cord and safety plug
- Strobe effect
- Control via stand-alone; DMX; sound to light via microphone
- Preprogrammed in Light'J; LED PC-Control 512
- With a beam angle of 21°

#### EUROLITE DMX LED Operator IR2DMX

IR control module to control 4 RGB spotlights and KLS sets

- DMX controller for LED devices with infrared receiver
- Suitable for matching EUROLITE IR remote (optional accessory, required for use)

### Logistic

- Inexpensive solution for controlling LED effects with 5-channel standard DMX protocol or KLS spotlight sets
- 4 LED parcans, one KLS light set and one LED BAR can be controlled at the same time
- Functions: static colors, automatic color change, internal programs, strobe effect, Master/Slave
- 47 control channels
- 3-pin XLR DMX output
- Control in stand-alone mode and DMX programming
- Sound-control via built-in microphone
- Adjustable microphone sensitivity via remote control
- Can transmit up to 47 DMX channels
- Control via IR remote control (optional); DMX; sound to light via microphone
- Interface
- For further information about this product, please refer to the Data Sheet under "Downloads"

#### EUROLITE IR-Remote for LED-Devices

Addressing and programming via infrared

- Operable up to 10 m
- Functions: programming of RGB dimming, Master/Slave function, DMX mode, DMX addressing as well as internal programs, auto mode, strobe effect with adjustable speed
- Control via IR remote control

##### Package contents

- 1 x remote control, 1 x battery

#### OMNITRONIC XLR Cable 3-pin 3m bk

Audio cable with 3-pin XLR connectors

- 1 x XLR cable

#### OMNITRONIC XLR Cable 3-pin 10m bk

Audio cable with 3-pin XLR connectors

- 1 x XLR cable

### Technical specifications:

Weight:	7,15 kg
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

#### EUROLITE LED PAR-56 RGB 5mm Short 5CH bk

Power supply:	230 V AC, 50 Hz
Power consumption:	23 W
IP classification:	IP20
Lamp type:	LED lamp
DMX channels:	3
Control:	Stand-alone; DMX; sound to light via microphone
Preprogrammed in:	Light´J; LED PC-Control 512
Beam angle:	21°
Beam angle (1/2 peak):	21°
Housing color:	Black

Dimensions:	Width: 20,5 cm Depth: 16,5 cm Height: 24 cm
Weight:	1,46 kg
DMX-control-channels:	5
DMX-512-connection:	3-pin XLR
Sound-control:	via built-in microphone
LED type:	5 mm
LED number:	151 (51 x red, 49 x green, 51 x blue)
Beam angle:	21°
Dimensions (L x W x H):	165 x 205 x 240 mm
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

#### **EUROLITE DMX LED Operator IR2DMX**

Power supply:	100-240 V AC, 50/60 Hz 9V DC 500 mA
Power consumption:	6,00 W
IP classification:	IP20
Power connection:	Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided)
DMX channels:	Output 47
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	IR remote control (optional); DMX; sound to light via microphone
Housing color:	Black
Color:	Black
Housing design:	Interface
Dimensions:	Width: 11 cm Depth: 10 cm Height: 3,5 cm
Weight:	0,33 kg

#### **EUROLITE IR-Remote for LED-Devices**

Control:	IR remote control
Dimensions:	Width: 4,6 cm Depth: 11 cm Height: 0,7 cm
Weight:	0,02 kg
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in

#### **OMNITRONIC XLR Cable 3-pin 3m bk**

Cable construction:	2 x 0,22 mm² microphone cable
Cable length:	3 m
Plug A:	1 x 3-pin XLR (M)
Plug B:	1 x 3-pin XLR (F)
Material:	Metal
Color:	Black
Dimensions:	Diameter: Ø 0,60 cm
Weight:	0,16 kg

#### **OMNITRONIC XLR Cable 3-pin 10m bk**

Cable construction:	Audio cable
Cable length:	10 m
Plug A:	1 x 3-pin XLR (M)
Plug B:	1 x 3-pin XLR (F)
Color:	Black
Weight:	0,46 kg