



Features:

EUROLITE LED KLS-801 Compact Light Set

Bar with 4 spots with 7 x 3 W 3in1 LED (RGB) each and carrying bag

- Complete LED light set with four slimline LED spots
- Crossbar with integrated DMX control unit
- Installation via TV pin for tripods with 28 mm interior diameter
- Ultra-light ideally suited for mobile use
- Comes pre-assembled with practical transport bag
- 7 TCL LEDs per spot
- Through the close chip placement of the multichip technology, an exquisite color mix even with short distances to the illuminated surface is provided
- Movable and tiltable spotlights
- DMX-controlled operation or stand-alone operation with processor-controlled color change
- Master/Slave operation
- Sound-control via built-in microphone with sensitivity control
- Convenient control possible via optional 4-pedal foot pedal FP-1 or IR remote control
- Optimized for control with the optional control panel DMX LED Operator 4
- Via DMX, each spot can be individually controlled
- DMX functions: dimmer, automatic mode, music control, strobe effect
- Addressing and setting via control panel with 4-digit LED display
- Suited for installation on a lighting stand (not included) or truss
- Black lacquered metal version
- Ideal for bands, stages or solo entertainers
- Ready for connection with power cord and safety plug
- 4 IEC outputs for power supply of further devices
- 7 LEDs 3 W high-power 3in1 R/G/B (homogenous color mix)-BR> spots controlled separately
- Control via stand-alone; DMX; foot switch (optional); sound to light via microphone

Logistic

- With a beam angle of 30°
- TV spigot
- For further information about this product, please refer to the Data Sheet under "Downloads"

EUROLITE DMX LED Operator IR2DMX

IR control module to control 4 RGB spotlights and KLS sets

- DMX controller for LED devices with infrared receiver
- Suitable for matching EUROLITE IR remote (optional accessory, required for use)
- Inexpensive solution for controlling LED effects with 5-channel standard DMX protocol or KLS spotlight sets
- 4 LED parcans, one KLS light set and one LED BAR can be controlled at the same time
- Functions: static colors, automatic color change, internal programs, strobe effect, Master/Slave
- 47 control channels
- 3-pin XLR DMX output
- Control in stand-alone mode and DMX programming
- Sound-control via built-in microphone
- Adjustable microphone sensitivity via remote control
- Can transmit up to 47 DMX channels
- Control via IR remote control (optional); DMX; sound to light via microphone
- Interface
- For further information about this product, please refer to the Data Sheet under "Downloads"

EUROLITE IR-Remote for LED-Devices

Addressing and programming via infrared

- Operable up to 10 m
- Functions: programming of RGB dimming, Master/Slave function, DMX mode, DMX addressing as well as internal programs, auto mode, strobe effect with adjustable speed
- Control via IR remote control

Technical specifications:

Weight:	12.10 kg
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE LED KLS-801 Compact Light Set

Power supply:	230 V AC, 50 Hz
Power consumption:	90.00 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	4 x IEC connector (F) mounting version fused 1 x IEC connector (F) mounting version Bypass
Lamp type:	LED lamp
LED type:	7 x 3 W high-power 3in1 R/G/B (homogenous color mix)
DMX channels:	15
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version

Control:	Stand-alone; DMX; foot switch (optional); sound to light via microphone
Fixtures available for:	Light J; LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
Beam angle (1/2 peak):	30°
Housing color:	Black
Attachment system:	TV spigot Ø 28mm
Weight:	11.75 kg
Dimensions:	Width: 120 cm Depth: 6.5 cm Height: 31.5 cm
Dimensions:	Width: 125 cm Depth: 12 cm Height: 38 cm
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE DMX LED Operator IR2DMX

Power supply:	100-240 V AC, 50/60 Hz 9V DC 500 mA
Power consumption:	6.00 W
Power connection:	Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided)
DMX channels:	Output 47
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	IR remote control (optional); DMX; sound to light via microphone
Housing color:	Black
Color:	Black
Housing design:	Interface
Dimensions:	Width: 11 cm Depth: 10 cm Height: 3.5 cm
Weight:	0.33 kg

EUROLITE IR-Remote for LED-Devices

Control:	IR remote control
Dimensions:	Width: 4.6 cm Depth: 11 cm Height: 0.7 cm
Weight:	0.02 kg
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in

Scope of delivery:

1 x EUROLITE LED KLS-801 Compact Light Set

- 1 x spotlight
- 1 x bag

1 x EUROLITE IR-Remote for LED-Devices

- 1 x remote control
- 1 x battery