

## **FUTURELIGHT Set 2x EYE-7 BEAM**

4in1 moving-head beam with 15 W LEDs

Art. No.: 09000234

GTIN:



## The article is no longer in our assortment.

Features: Logistic

- Equipped with 7 x 15 W quadcolor LED with RGBW colors (Osram)
- Compact housing
- Narrow illumination angle
- High PAN/TILT speed
- Supports RDM (Remote Device Management)
- 14, 16 or 22 DMX channels selectable
- Exact positioning via 16 bit PAN/TILT movement resolution, dimmer intensity and colors
- Master dimmer
- Color presets
- Stepless RGBW color mixture
- Strobe effect with adjustable speed
- Random strobe effect
- Automatic position correction
- PAN angle switchable between 540° and 630°
- Sound-controlled via built-in microphone
- Switch-mode power supply
- Automatic power supply adaption between 100 and 240 Volts without power selector
- Control board with graphic LCD display and foil-keyboard for adjusting the DMX-starting address, PAN/TILT reverse, reset
- DMX-controlled operation or stand-alone operation with Master/Slave function
- The scenes can be modified via the Control Board or via an external controller and loaded into the memory
- Number of scenes can be changed individually
- Software upload by optional accessories via DMX link
- Power connection via Neutrik PowerCon jack and included power cable
- Feed-through output allows to power another device

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted. Illustration only. Actual item may differ from photo.

- After every 8 device the fixtures must have a renewed connection with the power mains
- DMX control via every standard DMX controller

## **Technical specifications:**

Weight:	12,80 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

## FUTURELIGHT EYE-7 RGBW LED Moving-Head Beam

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	100,00 W
Dimensions:	Width: 17,9 cm
	Depth: 35 cm
	Height: 24,4 cm
DMX channels:	14/16/22
DMX connection:	3-pin XLR
Sound-control:	via built-in microphone
Flash-rate:	18 Hz
LED number:	7
LED type:	15 W QCL
Beam angle:	7°
Maximum PAN-movement:	630°
Maximum TILT-movement:	270°
Dimensions (L x W x H):	244 x 179 x 350 mm
Weight:	6 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting