

The article is no longer in our assortment.

Features:

EUROLITE LED SLS-3 HCL 3x10W Floor

Slimline LED spot with 3 x 10 W 5in1 LED

- Operable in stand-alone mode or via DMX interface
- DMX512 control possible via any commercial DMX controller (occupies max. 9 channels)
- Master/Slave for parallel operation of several devices
- 6, 7, 8 or 9 DMX channels selectable for numerous applications
- Sound-control via built-in microphone
- Equipped with 6in1 hexacolor LEDs for homogeneous light output in the colors red, green, blue, amber, white and UV
- Flat housing form requires minimal space when rigging
- Second mounting bracket for safe standing installation
- Functions: Static colors, RGBAW+UV color blend, internal programs, dimmer, strobe, sound-control, microphone sensitivity, color macros
- Further display settings: display on or off, display inverted, default settings
- Comfortable addressing and setting via control panel with 4-digit LED screen and four operating buttons
- Ready for connection via IEC power cord with safety-plug
- Feed-through output allows to power up to 8 devices
- Switch-mode power supply for operation between 100 and 240 volts
- Preprogrammed in Light´J; Light Captain

EUROLITE DMX LED Operator 6 Controller

Simple controller for 6 RGBWA+UV LED spots

- DMX controller for easy operation of standard 6-channel LED spots

Logistic

- 6 spots or light effect units with RGBWA+UV LEDs can be controlled
- 6 DMX channels (red/green/blue/white/amber/UV) can be controlled per unit
- Sequence of white and amber function freely selectable
- 6 trigger buttons for direct color selection and preset chases
- 18 trigger buttons for color presets
- Internal memory for 1 scene
- Auto, fade and macro mode
- Fade and speed time can be adjusted separately
- Master fader
- Strobe function with adjustable speed
- Blackout function
- Desktop console
- Can transmit up to 36 DMX channels
- Control via DMX; sound to light via microphone
- Desktop console housing

ROADINGER Flightcase 4x SLS Size M

Trunk case, PRO version

- Individually adjustable and removable dividers for universal use
- With 4 device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- Hinged, chromium plated case handle
- 2 chrome tip-over locks
- 1 high-quality butterfly lock
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

OMNITRONIC XLR Cable 3-pin 5m bk

Audio cable with 3-pin XLR connectors<p class='attributgroup'>Package contents

- 1 x XLR cable

OMNITRONIC XLR Cable 3-pin 10m bk

Audio cable with 3-pin XLR connectors<p class='attributgroup'>Package contents

- 1 x XLR cable

Technical specifications:

EUROLITE LED SLS-3 HCL 3x10W Floor

| | |
|--------------------|---|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 24,00 W |
| Preprogrammed in: | Light´J; Light Captain |
| Dimensions: | Width: 11,5 cm Depth: 21 cm Height: 22,5 cm |
| DMX channels: | 6/7/8/9 |
| DMX connection: | 3-pin XLR |
| Sound-control: | via built-in microphone |
| LED type: | 10 W HCL |
| LED number: | 3 |
| Beam angle: | 40° |

| | |
|-------------------------|--|
| Dimensions (W x D x H): | 115 x 210 x 225 mm |
| Weight: | 2 kg |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

EUROLITE DMX LED Operator 6 Controller

| | |
|--------------------|---|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Pin configuration: | Inside + / outside - |
| Power consumption: | 4 W |
| IP classification: | IP20 |
| Protection class: | Protection class III |
| Power connection: | Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided) |
| DMX channels: | Output 36 |
| DMX output: | 1 x 3-pin XLR (F) mounting version |
| Control: | DMX; sound to light via microphone |
| Housing color: | Black |
| Color: | Black |
| Housing design: | Desktop console housing |
| Dimensions: | Width: 40 cm Depth: 15 cm Height: 7 cm |
| Weight: | 1,60 kg |

ROADINGER Flightcase 4x SLS Size M

| | |
|--------------------------|---|
| Maximum load: | 25 kg |
| Aluminum profile frames: | 30 mm |
| Case handle: | 1 pc/pcs |
| Stop hinge: | 2 pc/pcs |
| Lock: | Butterfly lock: 1 pc/pcs |
| Use of brands: | Branded hardware |
| Material: | Birch multiplex, 7 mm |
| Color: | Dark brown, laminated |
| Compartment dimensions: | 12 cm x 25 cm x 35,5 cm |
| Inside dimensions: | 49,5 cm x 25 cm x 35,5 cm |
| Dimensions: | Width: 52,5 cm Depth: 28,5 cm Height: 44,5 cm |
| Weight: | 7,65 kg |

OMNITRONIC XLR Cable 3-pin 5m bk

| | |
|---------------------|-------------------------------|
| Cable construction: | 2 x 0,22 mm² microphone cable |
|---------------------|-------------------------------|

| | |
|---------------|---------------------|
| Cable length: | 5 m |
| Plug A: | 1 x 3-pin XLR (M) |
| Plug B: | 1 x 3-pin XLR (F) |
| Material: | Metal |
| Color: | Black |
| Dimensions: | Diameter: Ø 0,60 cm |
| Weight: | 0,24 kg |

OMNITRONIC XLR Cable 3-pin 10m bk

| | |
|---------------------|-------------------|
| Cable construction: | Audio cable |
| Cable length: | 10 m |
| Plug A: | 1 x 3-pin XLR (M) |
| Plug B: | 1 x 3-pin XLR (F) |
| Color: | Black |
| Weight: | 0,46 kg |