



The article is no longer in our assortment.

Features:

EUROLITE LED Pixel Tube 360° clear 1.5m

DMX LED tube for truss installation or ceilings

- Lightweight plastic tube
- 26 individually controllable pixels (illumination units with 4 LED each)
- Stepless color blend, color change, dimmer and strobe effect
- 4 LED Pixel Tubes 360° can be used with one controller
- 104 powerful LEDs SMD 5050 3in1 TCL RGB (homogenous color mix)
- Control via ArtNet; stand-alone; DMX
- With a beam angle of 360°
- For application areas such as: Clubs/dancing school; Stage

EUROLITE LED PSU-24V/4 DC LED Tube 360°

Controller for EUROLITE LED Pixel Tubes 360°

- Controller and power supply unit for 4 LED light tubes
- Color change adjustable; Dimmer electronic; color blend stepless
- Strobe effect
- Control via stand-alone; DMX; Sound to light via Microphone; Master/slave function
- 3 digit 7-segment LED display
- Preprogrammed in LED PC-Control 512

Package contents

- 1 x device, 1 x user manual, 1 x power cord

Logistic

Technical specifications:

Legal specifications

Special product: Not designed for household room illumination

Intended use: Show effect lighting

EUROLITE LED Pixel Tube 360° clear 1.5m

Power supply: 24 V DC

Power consumption: 18,00 W

LED: 104 x SMD 5050 3in1 TCL RGB (homogenous color mix)

Control: ArtNet; stand-alone; DMX

Beam angle: 360°

Beam angle (1/2 peak): 360°

Dimensions: Length: 1,53 m
Diameter: Ø 5 cm

Weight: 700 g

Legal specifications

Special product: Not designed for household room illumination

Intended use: Show effect lighting

EUROLITE LED PSU-24V/4 DC LED Tube 360°

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 95,00 W

Power connection: Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)

Power output: 1 x IEC connector (F) mounting version

DMX channels: 5; 7; 14; 84; 192; 312

DMX input: 1 x 3-pin XLR (M) mounting version

DMX output: 1 x 3-pin XLR (F) mounting version

Control: Stand-alone; DMX; Sound to light via Microphone; Master/slave function

Preprogrammed in: LED PC-Control 512

Maximum connection: 4 tubes

Display type: 3 digit 7-segment LED display

Output: 24 V DC;

Dimensions: Width: 24 cm
Depth: 29 cm
Height: 6 cm

Weight: 2,05 kg
