



### Features:

### Logistic

#### FUTURELIGHT LED PXS-20 Artnet Strip

LED bar for video and pixel mapping applications via Art-Net

- Modular LED strip with 20 pixels for video and pixel mapping applications via Art-Net
- Data and power supply via optional video processor
- Extra bright and colorful projection of videos, animations and graphics
- Modular concept allows the build-up of large areas
- Ideal for rental companies, stage/fair construction and fixed installation
- For use with MADRIX or any other lighting control software supporting Art-Net
- RGB SMD 5050 LEDs, covered by a smooth diffuser plate, provide excellent color rendering and wide viewing angles
- Signal distribution via UTP cable
- Movable mounting bracket for flexible installation
- 20 LEDs SMD 5050 3in1 R/G/B (homogenous color mix)
- The device is cooled by passive convection cooling
- Control via RDM; Art-Net
- With a beam angle of 120°

#### FUTURELIGHT PSU-16 Artnet Controller

Video processor for LED PXS-40 + PXS-20 Art-Net Strip

- Video processor and power supply unit for LED PXS-40/20 Artnet Strip
- For use with MADRIX or any other lighting control software supporting Art-Net
- Connections for 16 LED PXS-40 Artnet Strips
- 2 x 16-digit LCD screen for menu settings
- Integrated web interface for comfortable configuration and firmware updates through a browser

- Useful software tool scans the network and identifies fixtures
- Neutrik PowerCon input and output
- Signal distribution via UTP cable
- Switch-mode power supply for operation between 100 and 240 volts
- Control via Art-Net; RDM

## Technical specifications:

---

Weight: 44.35 kg

---

### FUTURELIGHT LED PXS-20 Artnet Strip

Power supply:	28V DC
Power consumption:	10.00 W
Lamp type:	LED lamp
LED type:	20 x SMD 5050 3in1 R/G/B (homogenous color mix)
DMX channels:	60
Network connection:	Protocol: Art-Net 3 via 2x RJ-45 (F) mounting version
Cooling:	Passive convection cooling
Control:	RDM; Art-Net
Beam angle (1/2 peak):	120°
Image:	20 px Pixel pitch 25 mm Brightness 850cd/m <sup>2</sup>
Housing color:	Black
Dimensions:	Length: 50 cm Depth: 3.8 cm Height: 14 cm
Weight:	1.30 kg
Display refresh rate:	400 Hz
Video refresh rate:	60 fps
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

### FUTURELIGHT PSU-16 Artnet Controller

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	300.00 W
Network connection:	Protocol: Art-Net 3 via 2x RJ-45 (F) mounting version
Control:	Art-Net; RDM
Housing color:	Black
Connections:	Signal via 4 x RJ-45 (F) mounting version
Dimensions:	Width: 26 cm

Depth: 22.6 cm

Height: 8 cm

---

Weight:

2.75 kg

---

**Scope of delivery:**

---