



The article is no longer in our assortment.

Features:

EUROLITE PAR-64 Spot Long with Cable bk

Long PAR-64 housing (with open cable ends)

- Durable aluminum cabinet
- Strong aluminum mounting bracket
- Heat-resistant fixing screw
- The screw is protected against turning it too far out
- 4 clip-to-hold clamps with spring locks for comfortable opening of the color filter frame
- Safety grille (splinter protection) is integrated in the tube
- Blackened tube for precise light output
- Strong brass clamps with extension spring for safe hold and for quick opening of the rear housing cover
- Protection grille on the rear housing cover - complies with CE regulations
- Comes fully-wired with black silicone cable, stable earthing in the housing and directly clamped ceramic socket
- Color filter frame included in delivery
- Strong cable tension relief
- Well-suited for easy installation of our Raylight reflectors with matching connector (GX16)
- Simple mounting: connect with ceramic socket - ready!
- Power plug has to be ordered separately; delivery is with open cable ends; delivery is with open cable ends; delivery is with open cable ends; delivery is with open cable ends; delivery is with open cable ends
- For PAR 64

Package contents

- 1 x spotlight, 1 x filter frame, 1 x lamp clamping ring, 1 x user manual

Logistic

OMNILUX PAR-64 240V/1000W GX16d NSP 300h H

PAR-64 lamp (Halogen)

- Harmless for color-foils
- The heat permeates the front-glass continuously
- Dimmable
- Hot restrike
- Very high color rendering index (CRI)
- For application areas such as: Video and photography; Clubs/dancing school; Stage

Technical specifications:

Weight:	3,51 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE PAR-64 Spot Long with Cable bk

Power supply:	230 V AC, 50 Hz
Power consumption:	Max. 1000 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Fixed Supply cord with open wires
Cable length:	Approx. 0,7 m
Base:	GX16d
Lamp type:	Selectable
Color generation:	Via color filter frame (optional)
Housing color:	Black
Slot for spot length:	25,7 cm x 25,7 cm
Dimensions:	Length: 42,5 cm Width: 26,5 cm Height: 27 cm
Weight:	1,97 kg
Filter frame	
Dimensions:	Length: 25,5 cm Width: 25,5 cm Diameter: Ø 20,2 cm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

OMNILUX PAR-64 240V/1000W GX16d NSP 300h H

Operating voltage:	240 V, 220 - 240 V
--------------------	--------------------

Nominal wattage:	1000 W
Base:	GX16d
Lamp type:	Halogen lamp; clear lamp; high voltage lamp; sealed beam lamp; halogen bulb
Lamp specification:	Dimmable Hot restrike
Beam angle:	11°
Color of light:	White
Color temperature:	3000K
Color rendering index (CRI):	95 Ra
Lead time:	0 s
Construction:	PAR-64
Operating temperature max.:	40° C
Operating temperature min.:	20° C
Burning position:	S180 (universal)
Lamp life:	300 h
Luminous flux:	18700 lm
Dimensions (LxD):	152x203 mm
Weight:	770 g
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting