



Features:

EUROLITE PAR-64 Spot Long with Cable sil

Long PAR-64 housing (with open cable ends)

- 4 clip-to-hold clamps with spring locks for comfortable opening of the color filter frame
- Safety grille (splinter protection) is integrated in the tube
- Strong clamps with extension springs for safe hold and for quick opening of the rear housing cover
- Blackened tube for precise light output
- Strong cable tension relief
- With mounting bracket
- Available in various colors
- For PAR 64
- For application areas such as: Advertisement/Shop window; decoration; clubs/dancing school

Logistic

EUROLITE Raylight PAR-64,GY-9.5 Socket long

The alternative to traditional lamps

- Immediately and without changing the wiring, exchangeable by flanged on pin socket (GX 16) against a PAR-64 lamp
- Cost savings, as only the burner must be replaced at a lamp change
- Longlife lamp types (up to 2.000 h) also save time and money
- Low weight

OMNILUX A1 230V/500W GY-9.5 75h

Special lamp for show effect lighting

- One-sided base
- Easy lamp replacement
- Dimmable
- Very high color rendering index (CRI)

Technical specifications:

Weight:	1.79 kg
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE PAR-64 Spot Long with Cable sil

Power supply:	230 V AC, 50 Hz
Power consumption:	Max. 1000 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Fixed supply cord with open wires
Cable length:	Approx. 0.7 m
Base:	GX16d
Lamp type:	Selectable
Color generation:	Via color filter frame (optional)
Housing color:	Silver
Attachment system:	Mounting bracket
Slot for spot length:	25.7 cm x 25.7 cm
Dimensions:	Length: 41.5 cm Width: 26.5 cm Height: 34.5 cm
Weight:	1.63 kg
Dimensions:	Length: 25.5 cm Width: 25.5 cm Diameter: Ø 20.2 cm
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE Raylight PAR-64,GY-9.5 Socket long

Power supply:	230 V AC, 50 Hz
Power consumption:	500 W
Base:	GY9.5; GX16d
Beam angle (1/2 peak):	NSP
Color:	Alu colored
Dimensions:	Diameter: Ø 20.3 cm
Weight:	0.14 kg

OMNILUX A1 230V/500W GY-9.5 75h

Voltage (lamps):	230 V, AC
Nominal wattage:	500 W
Base:	GY9.5
Lamp type:	Halogen lamp
Lamp specification:	Dimmable
Beam angle:	310°
Color of light:	White
Color temperature:	2700K
Color rendering index (CRI):	100 Ra
Lead time:	0.2 s
Construction:	Bi pin
Operating temperature max.:	40° C
Operating temperature min.:	20° C
Burning position:	S180 (universal)
Lamp life:	75 h
Luminous flux:	7200 lm
Wavelength:	778 nm
Lamp current:	2.17 A
Dimensions (LxD):	78x18 mm
Weight:	0.02 kg
Energy efficiency class (A - G):	G
EPREL-Nr:	1519666

Scope of delivery:

1 x spotlight
1 x filter frame
1 x lamp clamping ring
1 x user manual