



### Features:

#### EUROLITE PAR-30 Spot black

PAR-30 housing with E27 socket (with plug + cable)

- 4 clip-to-hold clamps with spring locks for comfortable opening of the color filter frame
- Strong clamps with extension springs for safe hold and for quick opening of the rear housing cover
- Blackened tube for precise light output
- Suitable for different spot angles
- Small lighting-systems can also be realized with a small budget
- Control via plug and play
- With mounting bracket
- For PAR 30
- For application areas such as: Clubs/dancing school; decoration; Trade fair and shop fitting; party room; restaurants, bars and hotels; advertisement/Shop window
- Silent operation

#### OMNILUX PAR-30 240V/100W E-27 spot

PAR-30 lamp

- Halogene lamp, suitable for E-27-socket (230 V~)
- Clear, brilliant halogene light for spot (10°) or Flood (30°)
- Operation at mains voltage without transformator
- Front screen provides for low bleaching and protects against contact with and soiling of burner
- Easy replacement with normal E-27 reflector lamps
- Average lifetime 2000 hours
- Constant light flow and no blackening of the burner during lifetime

### Logistic

- Any burner position possible
- Dimmable
- Hot restrike
- Very high color rendering index (CRI)

## Technical specifications:

---

|                  |  |
|------------------|--|
| Weight:          | 0.69 kg                                      |
| Special product: | Not designed for household room illumination |
| Intended use:    | Show effect lighting                         |

### EUROLITE PAR-30 Spot black

|                          |   |
|--------------------------|---|
| Power supply:            | 230 V AC, 50 Hz   |
| Power consumption:       | Max. 100 W  |
| IP classification:       | IP20  |
| Protection class:        | Protection class I                                      |
| Suitable lamp:           | Max. 230 V/100 W E27                                    |
| Power connection:        | Fixed power supply cord with safety plug                |
| Cable construction:      | 3 x 0.75 mm <sup>2</sup> H05SS-F                        |
| Cable length:            | Approx. 0.4 m   |
| Base:                    | E27   |
| Lamp type:               | Selectable  |
| Color generation:        | Via color filter frame                                  |
| Control:                 | Plug and play   |
| Construction:            | PAR-30  |
| Housing color:           | Black matte   |
| Attachment system:       | Mounting bracket  |
| Material:                | Aluminum  |
| Slot for spot length:    | 12.8 cm x 12.8 cm                                       |
| Dimensions:              | Length: 23.5 cm<br>Width: 14.5 cm<br>Height: 21 cm      |
| Weight:                  | 0.53 kg   |
| Noise classification:    | Class 0 (no noise at all)                               |
| Diameter mounting holes: | 2 x Ø10mm   |
| Material:                | Aluminum, 3 mm  |
| Color:                   | Black, matte  |
| Shape:                   | Octagonal   |
| Material:                | Aluminum, 0.5 mm  |
| Color:                   | Black, matte  |
| Dimensions:              | Length: 12.6 cm<br>Width: 12.6 cm<br>Diameter: Ø 9.4 cm |
| Weight:                  | 0.022 kg  |

**OMNILUX PAR-30 240V/100W E-27 spot**

|                                    |  |
|------------------------------------|--|
| Voltage (lamps):                   | 240 V, AC  |
| Nominal wattage:                   | 100 W  |
| Base:                              | E27  |
| Lamp type:                         | Halogen lamp; clear lamp; high voltage lamp;<br>reflector lamp; halogen bulb |
| Lamp specification:                | Dimmable<br>Hot restrike   |
| Beam angle:                        | 10°  |
| Color of light:                    | White  |
| Color temperature:                 | 2700K  |
| Color rendering index (CRI):       | 95 Ra  |
| Lead time:                         | 0 s  |
| Construction:                      | PAR-30   |
| Operating temperature max.:        | 40° C  |
| Operating temperature min.:        | 20° C  |
| Burning position:                  | S180 (universal)   |
| Lamp life:                         | 2000 h   |
| Luminous flux:                     | 800 lm   |
| Dimensions (LxD):                  | 92x95 mm   |
| Energy efficiency class (A++ - E): | D  |

**Scope of delivery:**

1 x spotlight  
1 x filter frame  
1 x user manual