



The article is no longer in our assortment.

Features:

EUROLITE PAR-56 Spot Long With PAR-Safe sil

Classic spotlight

- Rugged metal housing
- Heat-resistant fixing screw
- The screw is protected against turning it too far out
- If the screw is loosened the spot remains in its position due to the brake
- 4 clip-to-hold clamps with spring locks for comfortable opening of the color filter frame
- Safety grille (splinter protection) is integrated in the tube
- Blackened tube for precise light output
- Strong extension spring for safe hold and for quick opening of the rear housing cover
- Strong cable tension relief
- With Mounting bracket
- For PAR 56

Package contents

- 1 x spotlight, 1 x filter frame, 1 x lamp clamping ring, 1 x user manual

OMNILUX PAR-56 230V/300W NSP 2000h H

Special lamp for show effect lighting

- Dimmable
- Hot restrike
- Very high color rendering index (CRI)

Logistic

Technical specifications:

Weight:	2,04 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE PAR-56 Spot Long With PAR-Safe sil

Power supply:	230 V AC, 50 Hz
Power consumption:	Max. 500 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Fixed Supply cord with open wires
Base:	GX16d
Lamp type:	Selectable
Color generation:	Via color filter frame (optional)
Housing color:	Silver
Attachment system:	Mounting bracket
Color:	Black
Dimensions:	Width: 35 cm Depth: 25 cm Height: 30 cm
Weight:	1,48 kg
Filter frame	
Dimensions:	Length: 22,5 cm Width: 22,5 cm Diameter: Ø 17,6 cm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

OMNILUX PAR-56 230V/300W NSP 2000h H

Operating voltage:	230 V, 220 - 240 V
Nominal wattage:	300 W
Base:	GX16d
Lamp type:	Halogen lamp; clear lamp; high voltage lamp; sealed beam lamp; halogen bulb
Lamp specification:	Dimmable Hot restrike
Beam angle:	10°
Color of light:	White

Color temperature:	2750K
Color rendering index (CRI):	95 Ra
Lead time:	0 s
Construction:	PAR-56
Operating temperature max.:	40° C
Operating temperature min.:	20° C
Burning position:	S180 (universal)
Lamp life:	2000 h
Luminous flux:	3500 lm
Dimensions (LxD):	127x178 mm
Weight:	560 g