



The article is no longer in our assortment.

Features:

EUROLITE PAR-56 Spot Long With PAR-Safe bk

Allrounder in long housing

- Rugged aluminum housing
- Strong aluminum mounting bracket with hole for fixing the obligatory safety rope
- Heat-resistant fixing screw for "bombproof" fixing
- The screw is protected against turning it too far out
- If the screw is loosened the spot remains in its position due to the brake
- 4 clip-to-hold clamps with spring locks for comfortable opening of the color filter frame
- Safety grille (splinter protection) is integrated in the tube
- Internally blackened tube for precise light output
- Strong extension spring for safe hold and for quick opening of the rear housing cover
- Protection grille on the rear housing cover - complies with CE-regulations
- Comes fully-wired with black silicone cable, stable earthing in the housing and directly clamped ceramic socket
- Delivered with color filter frame
- With strong cable tension relief
- Well-suited for easy installation of our Raylight reflectors with matching connector (GX16)
- Simple mounting: connect with ceramic socket - ready!
- Power plug has to be ordered separately; delivery is with open cable ends
- For PAR 56

OMNILUX PAR-56 230V/300W NSP 2000h H

Special lamp for show effect lighting

- Dimmable

Logistic

- Hot restrike
- Very high color rendering index (CRI)

Technical specifications:

Weight:	1,86 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE PAR-56 Spot Long With PAR-Safe bk

Power supply:	230 V AC, 50 Hz
Power consumption:	500 W
IP classification:	IP20
Housing color:	Black
Dimensions:	Width: 25 cm Depth: 30 cm Height: 35 cm
Weight:	1,30 kg
Dimensions (L x W x H):	350 x 250 x 300 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

OMNILUX PAR-56 230V/300W NSP 2000h H

Operating voltage:	230 V, 220 - 240 V
Nominal wattage:	300 W
Base:	GX16d
Lamp type:	Halogen lamp; clear lamp; high voltage lamp; sealed beam lamp; halogen bulb
Lamp specification:	Dimmable Hot restrike
Beam angle:	10°
Color of light:	White
Color temperature:	2750K
Color rendering index (CRI):	95 Ra
Lead time:	0 s
Construction:	PAR-56
Operating temperature max.:	40° C
Operating temperature min.:	20° C
Burning position:	S180 (universal)
Lamp life:	2000 h

Luminous flux:	3500 lm
Dimensions (LxD):	127x178 mm
Weight:	560 g