



The article is no longer in our assortment.

Features:

EUROLITE PAR-56 Spot Long with Cable bk

Long PAR-56 housing (with open cable ends)

- Rugged metal housing
- Blackened tube for precise light output
- Heat-resistant fixing screw
- The screw is protected against turning it too far out
- 4 clip-to-hold clamps with spring locks for comfortable opening of the color filter frame
- Safety grille (splinter protection) is integrated in the tube
- Strong extension spring for safe hold and for quick opening of the rear housing cover
- Strong cable tension relief
- With Mounting bracket
- For PAR 56

Package contents

- 1 x spotlight, 1 x filter frame, 1 x lamp clamping ring, 1 x user manual

Logistic

EUROLITE Raylight PAR-56,GY-9.5 Socket long

The alternative to traditional lamps

- Immediately and without changing the wiring, exchangeable by flanged on pin socket (GX 16) against a PAR-56 lamp
- Cost savings, as only the burner must be replaced at a lamp change
- Longlife lamp types (up to 2.000 h) also save time and money
- Low weight

OMNILUX A1 230V/500W GY-9.5 75h

Special lamp for show effect lighting

- One-sided base
- Easy lamp replacement
- Dimmable
- Hot restrike
- Very high color rendering index (CRI)

Technical specifications:

Weight:	1,45 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE PAR-56 Spot Long with Cable bk

Power supply:	230 V AC, 50 Hz
Power consumption:	Max. 500 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Fixed Supply cord with open wires
Cable length:	Approx. 0,7 m
Base:	GX16d
Lamp type:	Selectable
Color generation:	Via color filter frame
Housing color:	Black
Attachment system:	Mounting bracket
Dimensions:	Length: 36 cm Width: 23 cm Height: 23,5 cm
Weight:	1,30 kg
Filter frame	
Dimensions:	Length: 22,5 cm Width: 22,5 cm Diameter: Ø 17,6 cm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE Raylight PAR-56,GY-9.5 Socket long

Power supply:	230 V AC, 50 Hz
Power consumption:	500 W

Base:	GY9.5; GX16d
Beam angle (1/2 peak):	NSP
Color:	Alu colored
Dimensions:	Diameter: Ø 17,5 cm
Weight:	120 g

OMNILUX A1 230V/500W GY-9.5 75h

Operating voltage:	230 V, 220 - 240 V
Nominal wattage:	500 W
Base:	GY9.5
Lamp type:	Halogen lamp; clear lamp; high voltage lamp; halogen bulb
Lamp specification:	Dimmable Hot restrike
Beam angle:	310°
Color of light:	White
Color temperature:	3200K
Color rendering index (CRI):	95 Ra
Lead time:	0 s
Construction:	Bi pin
Operating temperature max.:	40° C
Operating temperature min.:	20° C
Burning position:	S180 (universal)
Lamp life:	75 h
Luminous flux:	7200 lm
Weight:	20 g
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting