



The article is no longer in our assortment.

Features:

EUROLITE PAR-56 Spot Short with Cable sil

PAR-56 housing with silicone cable and open cable ends

- Heat-resistant fixing screw
- The screw is protected against turning it too far out
- 4 clip-to-hold clamps with spring locks for comfortable opening of the color filter frame
- Strong cable tension relief
- The device is cooled by passive convection cooling
- With Mounting bracket
- For PAR 56

Package contents

- 1 x spotlight, 1 x filter frame, 1 x lamp clamping ring, 1 x user manual

Logistic

EUROLITE Raylight PAR-56,GY-9.5 Socket long

The alternative to traditional lamps

- Immediately and without changing the wiring, exchangeable by flanged on pin socket (GX 16) against a PAR-56 lamp
- Cost savings, as only the burner must be replaced at a lamp change
- Longlife lamp types (up to 2.000 h) also save time and money
- Low weight

GE M38 240V/300W GY-9.5 2000h

Studio-lamp for base GY9.5

- One-sided base

- Dimmable
- Hot restrike
- Very high color rendering index (CRI)
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	940 g
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE PAR-56 Spot Short with Cable sil

Power supply:	230 V AC, 50 Hz
Power consumption:	Max. 500 W
IP classification:	IP20
Protection class:	Protection class I
Suitable lamp:	Max. 230 V/500 W PAR-56
Power connection:	Fixed Supply cord with open wires
Cable construction:	3 x 0,75 mm ² H05SS-F
Cable length:	Approx. 0,8 m
Base:	GX16d
Lamp type:	Selectable
Color generation:	Via color filter frame
Cooling:	Passive convection cooling
Housing color:	Silver
Attachment system:	Mounting bracket
Material:	Aluminum
Slot for spot length:	21,4 cm x 21,8 cm
Dimensions:	Length: 26 cm Width: 23,5 cm Height: 22 cm
Weight:	800 g
Mounting bracket	
Diameter mounting holes:	2 x Ø13mm
Material:	Metal, 2 mm
Filter frame	
Diameter mounting holes:	4 x Ø8mm
Shape:	Octagonal
Grid size:	10 x 10 mm
Material:	Aluminum, 0,6 mm
Dimensions:	Length: 21,5 cm Width: 21,5 cm

Diameter: Ø 17,1 cm

Lamp clamping ring

Material: Steel, 4 mm

Color: Silver

Legal specifications

Special product: Not designed for household room illumination

Intended use: Show effect lighting

EUROLITE Raylight PAR-56,GY-9.5 Socket long

Power supply: 230 V AC, 50 Hz

Power consumption: 500 W

Base: GY9.5; GX16d

Beam angle (1/2 peak): NSP

Color: Alu colored

Dimensions: Diameter: Ø 17,5 cm

Weight: 120 g

GE M38 240V/300W GY-9.5 2000h

Operating voltage: 240 V, 220 - 240 V

Nominal wattage: 300 W

Base: GY9.5

Lamp type: Halogen lamp; clear lamp; high voltage lamp;
halogen bulb

Lamp specification: Dimmable
Hot restrike

Beam angle: 310°

Color of light: White

Color temperature: 2900K

Color rendering index (CRI): 100 Ra

Construction: Bi pin

Operating temperature max.: 40° C

Operating temperature min.: 10° C

Burning position: S180 (universal)

Lamp life: 2000 h

Luminous flux: 5500 lm

Dimensions (LxD): 80x29 mm

Weight: 20 g

Legal specifications

Special product: Not designed for household room illumination

Intended use: Show effect lighting
