



**The article is no longer in our assortment.**

### Features:

#### EUROLITE PAR-64 Spot Long with Cable bk

Long PAR-64 housing (with open cable ends)

- Durable aluminum cabinet
- Strong aluminum mounting bracket
- Heat-resistant fixing screw
- The screw is protected against turning it too far out
- 4 clip-to-hold clamps with spring locks for comfortable opening of the color filter frame
- Safety grille (splinter protection) is integrated in the tube
- Blackened tube for precise light output
- Strong brass clamps with extension spring for safe hold and for quick opening of the rear housing cover
- Protection grille on the rear housing cover - complies with CE regulations
- Comes fully-wired with black silicone cable, stable earthing in the housing and directly clamped ceramic socket
- Color filter frame included in delivery
- Strong cable tension relief
- Well-suited for easy installation of our Raylight reflectors with matching connector (GX16)
- Simple mounting: connect with ceramic socket - ready!
- Power plug has to be ordered separately; delivery is with open cable ends; delivery is with open cable ends; delivery is with open cable ends; delivery is with open cable ends; delivery is with open cable ends
- For PAR 64

#### Package contents

- 1 x spotlight, 1 x filter frame, 1 x lamp clamping ring, 1 x user manual

### Logistic

## EUROLITE Raylight PAR-64,GY-9.5 Socket long

The alternative to traditional lamps

- Immediately and without changing the wiring, exchangeable by flanged on pin socket (GX 16) against a PAR-64 lamp
- Cost savings, as only the burner must be replaced at a lamp change
- Longlife lamp types (up to 2.000 h) also save time and money
- Low weight

## OMNILUX A1 230V/500W GY-9.5 75h

Special lamp for show effect lighting

- One-sided base
- Easy lamp replacement
- Dimmable
- Hot restrike
- Very high color rendering index (CRI)

## Technical specifications:

---

Weight:	2,14 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

## EUROLITE PAR-64 Spot Long with Cable bk

Power supply:	230 V AC, 50 Hz
Power consumption:	Max. 1000 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Fixed Supply cord with open wires
Cable length:	Approx. 0,7 m
Base:	GX16d
Lamp type:	Selectable
Color generation:	Via color filter frame (optional)
Housing color:	Black
Slot for spot length:	25,7 cm x 25,7 cm
Dimensions:	Length: 42,5 cm Width: 26,5 cm Height: 27 cm
Weight:	1,97 kg
Filter frame	
Dimensions:	Length: 25,5 cm Width: 25,5 cm Diameter: Ø 20,2 cm
Legal specifications	
Special product:	Not designed for household room illumination

Intended use: Show effect lighting

---

**EUROLITE Raylight PAR-64,GY-9.5 Socket long**

Power supply: 230 V AC, 50 Hz

---

Power consumption: 500 W

---

Base: GY9.5; GX16d

---

Beam angle (1/2 peak): NSP

---

Color: Alu colored

---

Dimensions: Diameter: Ø 20,3 cm

---

Weight: 140 g

---

**OMNILUX A1 230V/500W GY-9.5 75h**

Operating voltage: 230 V, 220 - 240 V

---

Nominal wattage: 500 W

---

Base: GY9.5

---

Lamp type: Halogen lamp; clear lamp; high voltage lamp; halogen bulb

---

Lamp specification: Dimmable  
Hot restrike

---

Beam angle: 310°

---

Color of light: White

---

Color temperature: 3200K

---

Color rendering index (CRI): 95 Ra

---

Lead time: 0 s

---

Construction: Bi pin

---

Operating temperature max.: 40° C

---

Operating temperature min.: 20° C

---

Burning position: S180 (universal)

---

Lamp life: 75 h

---

Luminous flux: 7200 lm

---

Weight: 20 g

---

Legal specifications

---

Special product: Not designed for household room illumination

---

Intended use: Show effect lighting

---