



The article is no longer in our assortment.

Features:

OSRAM HSD 250/60 4ArXS GY-9.5 2000h

HMI / MSR / HMP / OMI lamps

- Extremely high light output
- Best color rendering
- Light output three to four times higher in comparison to filament light
- Light is generated via an arc between two electrodes
- Spectrum similar to daylight (between 4500 and 6500 K)
- Constant color temperature and color rendering behaviour over the whole lamp life
- Photographic industry
- Halogen metal evaporation lamps provide a spectrum composed of a lot of lines, in contrast to temperature radiators, as halogen-incandescent lamps
- Good color rendering index (CRI)
- For further information about this product, please refer to the Data Sheet under "Downloads"

Logistic

OMNILUX OSD 90V/250W GY-9.5 1500h 6700K

- For further information about this product, please refer to the Data Sheet under "Downloads"

OSRAM HMI 575/GS 95V/575W SFC-10 1000h

HMI / MSR / HMP / OMI lamps

- Extremely high light output
- Best color rendering
- Light output three to four times higher in comparison to filament light

- Light is generated via an arc between two electrodes
- Spectrum similar to daylight
- Constant color temperature and color rendering behaviour over the whole lamp life
- Halogen metal evaporation lamps provide a spectrum composed of a lot of lines, in contrast to temperature radiators, as halogen-incandescent lamps
- Dimmable
- Hot restrike
- Very high color rendering index (CRI)
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

OMNILUX OMI 575 95V/575W SFC-10 500h

HMI / MSR / HMP / OMI lamps

- Extremely high light output
- Best color rendering
- Light output three to four times higher in comparison to filament light
- Light is generated via an arc between two electrodes
- Spectrum similar to daylight
- Constant color temperature and color rendering behaviour over the whole lamp life
- Halogen metal evaporation lamps provide a spectrum composed of a lot of lines, in contrast to temperature radiators, as halogen-incandescent lamps
- Hot restrike
- Very high color rendering index (CRI)
- For further information about this product, please refer to the Data Sheet under "Downloads"

OSRAM HMI 1200W/DXS 100V/1200W SFC-15.5

HMI / MSR / HMP / OMI lamps

- Extremely high light output
- Best color rendering
- Light output three to four times higher in comparison to filament light
- Light is generated via an arc between two electrodes
- Spectrum similar to daylight
- Constant color temperature and color rendering behaviour over the whole lamp life
- Halogen metal evaporation lamps provide a spectrum composed of a lot of lines, in contrast to temperature radiators, as halogen-incandescent lamps
- Hot restrike
- Very high color rendering index (CRI)
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

OMNILUX OBA 1200 100V/1200W SFC-15 5600K

HMI / MSR / HMP / OMI lamps

- Extremely high light output
- Best color rendering
- Light output three to four times higher in comparison to filament light
- Light is generated via an arc between two electrodes
- Constant color temperature and color rendering behaviour over the whole lamp life
- Halogen metal evaporation lamps provide a spectrum composed of a lot of lines, in contrast to temperature radiators, as halogen-incandescent lamps
- Hot restrike
- Good color rendering index (CRI)
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 1,20 kg

Special product: Not designed for household room illumination

Intended use:	Show effect lighting
OSRAM HSD 250/60 4ArXS GY-9.5 2000h	
Voltage (lamps):	90 V
Nominal wattage:	250 W
Base:	GY9.5
Lamp type:	Metal vapour lamp
Color temperature:	6000K
Color rendering index (CRI):	85 Ra
Burning position:	S180 (universal)
Lamp life:	2000 h
Luminous flux:	17000 lm
Lamp current:	3,1 A
Dimensions (LxD):	108x23 mm
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

OMNILUX OSD 90V/250W GY-9.5 1500h 6700K

Voltage (lamps):	90 V
Nominal wattage:	250 W
Base:	GY9.5
Lamp type:	Metal vapour lamp
Color temperature:	6700K
Burning position:	S180 (universal)
Lamp life:	1500 h
Luminous flux:	16000 lm
Lamp current:	3,5 A
Dimensions (LxD):	108x22,5 mm
Weight:	0,03 kg
EPREL-Nr:	2033780
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

OSRAM HMI 575/GS 95V/575W SFc-10 1000h

Operating voltage:	95
Nominal wattage:	575 W
Base:	SFc10
Lamp type:	Metal vapour lamp
Lamp specification:	Dimmable Hot restrike
Color temperature:	6000K

Color rendering index (CRI):	90 Ra
Construction:	Double-sided socket
Burning position:	S180 (universal)
Lamp life:	1000 h
Luminous flux:	49000 lm
Lamp current:	7 A
Dimensions (LxD):	136x21 mm
Weight:	0,04 kg
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

OMNILUX OMI 575 95V/575W SFc-10 500h

Operating voltage:	95
Nominal wattage:	575 W
Base:	SFc10
Lamp type:	Discharge lamp
Lamp specification:	Hot restrike
Color temperature:	6500K
Color rendering index (CRI):	90 Ra
Construction:	Double-sided socket
Burning position:	S180 (universal)
Lamp life:	500 h
Luminous flux:	49000 lm
Lamp current:	7 A
Dimensions (LxD):	136x21 mm
Weight:	0,04 kg
Energy efficiency class (A - G):	G
EPREL-Nr:	1507637

OSRAM HMI 1200W/DXS 100V/1200W SFc-15.5

Operating voltage:	100
Nominal wattage:	1200 W
Base:	SFc15
Lamp type:	Discharge lamp
Lamp specification:	Hot restrike
Color temperature:	6000K
Color rendering index (CRI):	90 Ra
Burning position:	S180 (universal)
Lamp life:	1000 h
Luminous flux:	110000 lm
Lamp current:	13,8 A
Dimensions (LxD):	220x27 mm

Weight:	0,11 kg
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

OMNILUX OBA 1200 100V/1200W SFc-15 5600K

Operating voltage:	100
Nominal wattage:	1200 W
Base:	SFc15
Lamp type:	Metal vapour lamp; discharge lamp
Lamp specification:	Hot restrike
Color temperature:	5600K
Color rendering index (CRI):	80 Ra
Construction:	Double-sided socket
Burning position:	S180 (universal)
Lamp life:	750 h
Luminous flux:	110000 lm
Lamp current:	13,8 A
Dimensions (LxD):	220x28 mm
Weight:	0,12 kg
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting