



**The article is no longer in our assortment.**

### Features:

#### EUROLITE LED PMC-16x20W COB 3200K

PRO COB performance cluster with 4 x 4 matrix

- Equipped with 16 x 20 W COB LED
- 3200 K color temperature
- 3, 16 or 19 DMX channels selectable for various applications
- Each LED can be controlled individually
- Functions: built-in programs and strobe effect with variable speed, dimmer, Master/Slave
- DMX-controlled operation or stand-alone operation with Master/Slave function
- For use on stages, catwalks, crossbeam systems, or decoration
- Comfortable addressing and setting via control panel with LC display and four operating buttons
- Locking possibility at the mounting bracket
- Power connection via Neutrik PowerCon jack and included power cable
- Feed-through output allows to power another device
- After every 8 device the fixtures must have a renewed connection with the power mains
- DMX control via every standard DMX controller
- Control via stand-alone; DMX; Sound to light via Microphone
- Preprogrammed in LED PC-Control 512; Light Captain
- With a beam angle of 60°

### Logistic

#### ROADINGER Flightcase 2x PMC-16

PRO flightcase for 2 x PMC-16

- Compartments for 2 x PMC-16
- Suitable for 41606200 EUROLITE LED PMC-16x20W COB 3200K and 41606400 EUROLITE LED PMC-16x30W COB RGB

- Interior upholstered with foam
- High-quality workmanship with multiplex birch wood, dark brown laminated
- Aluminum profile frames (25 mm) with rounded edges
- Three-leg, large steel ball corners
- 2 hinges
- 2 high-quality butterfly locks
- 2 case handles
- Branded hardware
- For further information about this product, please refer to the Data Sheet under "Downloads"

## Technical specifications:

---

Weight:	24,60 kg
<hr/>	
Legal specifications	
<hr/>	
Special product:	Not designed for household room illumination
<hr/>	
Intended use:	Show effect lighting
<hr/>	

### EUROLITE LED PMC-16x20W COB 3200K

Power supply:	100-240 V AC, 50/60 Hz
<hr/>	
Power consumption:	275 W
<hr/>	
IP classification:	IP20
<hr/>	
Lamp type:	LED lamp
<hr/>	
Color temperature:	3200K
<hr/>	
Flash rate:	1 - 20 Hz
<hr/>	
DMX channels:	3; 16; 19
<hr/>	
Control:	Stand-alone; DMX; Sound to light via Microphone
<hr/>	
Preprogrammed in:	LED PC-Control 512; Light Captain
<hr/>	
Beam angle:	60°
<hr/>	
Beam angle (1/2 peak):	60°
<hr/>	
Housing color:	Black
<hr/>	
Dimensions:	Width: 31,5 cm Depth: 34,5 cm Height: 34,5 cm
<hr/>	
Weight:	8,20 kg
<hr/>	
DMX channels:	3/16/19
<hr/>	
DMX connection:	5-pin and 3-pin XLR
<hr/>	
Flash-rate:	20 Hz
<hr/>	
Sound-control:	via built-in microphone
<hr/>	
LED number:	16
<hr/>	
LED type:	Array 20 W, white
<hr/>	
Color temperature:	3200 K
<hr/>	
Beam angle:	60°
<hr/>	
Dimensions (W x D x H):	345 x 315 x 345 mm
<hr/>	
Legal specifications	
<hr/>	
Special product:	Not designed for household room illumination
<hr/>	

Intended use: Show effect lighting

---

**ROADINGER Flightcase 2x PMC-16**

Maximum load:	50 kg
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Dimensions:	Width: 39 cm Depth: 44,5 cm Height: 43 cm
Weight:	8,20 kg
Strength:	7 mm
Outside dimensions (W x D x H):	390 x 445 x 430 mm
Inside dimensions (W x D x H):	415 x 355 x 335 mm
Compartment dimensions (W x D x H):	355 x 200 x 335 mm