

## OMNITRONIC EM-312 Entertainment Mixer

Microphone line mixer, 6 mono channels + 3 stereo channels

Art. No.: 10007077

GTIN: 4026397653618



**List price: 196.35 €**

incl. 19% VAT.

### Description:

The EM-312 is a slim rack-mounted 12-channel mixer with 6 mic/line combo inputs and 6 additional line inputs. It has XLR outputs, a 6.3 mm mono output, a stereo RCA recording output, and a 6.3 mm monitoring output for the mic section. The EM-312 offers separate volume controls for all inputs in addition to volume control for the mono output and a master volume control. It has a 3-band equalizer and an adjustable priority function for microphone announcements through channel 1.

### Logistic

EAN / GTIN: 4026397653618

Weight: 3,54 kg

Length: 0.55 m

Width: 0.28 m

Height: 0.10 m

### Features:

- 6 mono mic/line input channels (combo jack), switchable
- 3 stereo line input channels (RCA)
- Phantom power can be switched on for each microphone input
- All input channels with separate level controls and signal LED
- Adjustable priority circuit for channel 1
- Balanced stereo XLR outputs and RCA outputs
- Adjustable monitor output
- Adjustable mono line output (6.3 mm jack)
- Master level control, 4-digit stereo LED level meter and 3-band equalizer
- Additional screw terminals for 24 V DC power input
- (19") 48.3 cm rack installation 1 U
- For application areas such as: Installation; restaurants, bars and hotels; Clubs/dancing school

#### Package contents

- 1 x device, 1 x power cord, 4 x foot, 1 x user manual

## Technical specifications:

Power supply:	230 V AC, 50 Hz Or 24 V
Power consumption:	12 W
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) Mains input via screw terminal
Device fuse:	5 x 20 mm, T 0,5 A Fuse replaceable
Frequency range:	20 - 22000 Hz
S/N ratio:	>103 dB
THD:	<0,03 % at 1 kHz
Phantom power:	21 V DC or 18 V DC
Impedance:	Input: mic/line 1,4 kOhm Input: line 10 kOhm Output: 120 Ohm
Control elements:	Power switch, Input sensitivity switch, tone control, level control per channel, Master control
Status LED:	Power, signal, master level meter, clip
Connections:	Input: mic/line via 6 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version) Input: line via 3 x stereo RCA Output: master via 2 x 3-pin XLR Output: mono via 1 x 6.3 mm jack socket (mono) mounting version Output: rec. via 1 x stereo RCA
Channels:	Input channel: 6 x mono with Mic-line switch via Combination socket (XLR/jack), channel control via Rotary dial, 3-band tone control EQ 80Hz/2,5kHz/12kHz, Input sensitivity switch  Input channel: 3 x stereo via RCA, channel control via Rotary dial, 3-band tone control EQ 80Hz/2,5kHz/12kHz  Master output: 1 x stereo via XLR, channel control via Rotary dial  Master output: 1 x mono via Jack, channel control via Rotary dial
Max. level:	Input: Microphone -19 dBu Input: line +21 dBu Output: +21 dBu
Color:	Black
Housing design:	(19") 48.3 cm rack installation 1 U
Dimensions:	Width: 48,3 cm Depth: 23 cm Height: 4,45 cm
Weight:	3,04 kg