

## OMNITRONIC EM-280 Entertainment Mixer

8-channel stereo mixer with 2 adjustable zone outputs, 19"

Art. No.: 10007097

GTIN: 4026397714340



**List price: 355.81 €**

incl. 19% VAT.

### Features:

- 1 additional XLR microphone input in channel 1
- Nominal input level switchable between +4dBu and -10 dBV
- Signal and overload indicators in each channel
- 4-digit stereo level meter for each bus output
- (19") 48.3 cm rack installation 1 U
- For application areas such as: Installation; restaurants, bars and hotels; Clubs/dancing school

#### Package contents

- 1 x mixer, 1 x user manual, 1 x power cord, 1 x rCA cable

### Logistic

EAN / GTIN: 4026397714340

Weight: 3,65 kg

Length: 0.50 m

Width: 0.33 m

Height: 0.11 m

### Technical specifications:

Power supply:	115/230 V AC, 50/60 Hz
Power consumption:	15 W
Protection class:	Protection class I
Power connection:	Power supply cord with safety plug (provided)
Device fuse:	5 x 20 mm, T 1 A Fuse replaceable
Frequency range:	20 - 20000 Hz
S/N ratio:	>92 dB line >65 dB Microphone
THD:	Line <0,9 % at 1 kHz
Gain:	Mic/line 18 dB

Housing color:	Black
Control elements:	Groundlift selector
Status LED:	Power, master level meter, signal, clip
Connections:	<p>Input: line via 8 x 6.3-mm-jack (bal.)</p> <p>Input: Microphone via 1 x 3-pin XLR</p> <p>Output: master via 2 x 6.3-mm-jack (bal.)</p> <p>Output: AUX via 1 x 6.3-mm-jack (bal.)</p> <p>Output: headphones via 1 x 6.3 mm jack socket (stereo) mounting version</p> <p>Output: headphones via 1 x 3.5 mm jack (stereo) mounting version</p>
Channels:	<p>Input channel: 1 x mono + stereo with Mic-line switch via XLR or jack, channel control via Rotary dial, pre-post switch, gain control</p> <p>Input channel: 7 x stereo via Jack, channel control via Rotary dial, pre-post switch</p> <p>Master bus input: 2 x stereo via Jack, Routing master bus switch</p> <p>Master output: 2 x mono + stereo via XLR or RCA, channel control via Rotary dial, stereo/mono switch</p> <p>Master bus output: 1 x stereo via Jack</p> <p>Headphones output: 1 x stereo via Jack, channel control via Rotary dial, Routing master bus switch</p>
Housing design:	(19") 48.3 cm rack installation 1 U
Dimensions:	<p>Width: 48,3 cm</p> <p>Depth: 28,0 cm</p> <p>Height: 4,4 cm</p>
Weight:	3,06 kg