

## OMNITRONIC EM-640B Entertainment Mixer

3-zone installation mixer, black

Art. No.: 10007106

GTIN: 4026397419160



**The article is no longer in our assortment.**

### Features:

- 3 zones with routing facility of all input channels as desired
- 4 input channels with gain controls, peak LED and smooth dual-rail channel faders
- 2 microphone channels with level control, 2-way equalizer, talkover and on/off button
- Prefader listening (cue) to stereo input channels and zone outputs via adjustable headphones output
- Zone outputs with level control, 3-way equalizer and 10-digit LED level meter
- Inputs: 6 x line (stereo RCA); 2 x line/phono (stereo RCA), switchable; 2 x microphone (XLR/6.3 mm jack) and headphones (6.3 mm jack)
- Outputs: 3 x master (optionally 3-pin XLR or stereo RCA)
- Operation via supplied power unit
- Rack installation, 4 U
- (19") 48.3 cm rack installation 4 U

### Logistic

EAN / GTIN: 4026397419160

Weight: 4,20 kg

Length: 0.60 m

Width: 0.24 m

Height: 0.16 m

### Technical specifications:

Power supply:	230 V AC, 50 Hz 12 V 1,5 A
Power consumption:	35,00 W
Protection class:	Protection class III
Power connection:	Mains input via Coaxial power connector (M) mounting version power supply cord with AC adapter (provided)
Frequency range:	20 - 20000 Hz

S/N ratio:	>65 dB
THD:	<0,03 % at 1 kHz
Control elements:	Power switch, Talkover
Status LED:	Master level meter, peak, CUE, power, Talkover; Routing, ON AIR
Connections:	Input: Microphone via 2 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version)  Input: line/phono via 2 x stereo RCA Input: line via 6 x stereo RCA Output: master via 3 x stereo RCA Output: master via 6 x 3-pin XLR Output: headphones via 1 x 6.3 mm jack (stereo)
Channels:	Microphon channel: 2 x mono via Combination socket (XLR/jack), channel control via Rotary dial, 2-band tone control EQ 100Hz/10kHz, gain control, Routing master bus switch, ON AIR switch, Talkover switch  Input channel: 2 x stereo with Line-Line/Phono switch via RCA, channel control via fader, 3-band tone control EQ 100Hz/1kHz/10kHz, gain control, Routing master bus switch, CUE switch  Input channel: 2 x stereo with Line-line switch via RCA, channel control via fader, gain control, Routing master bus switch, CUE switch  Master output: 3 x stereo via XLR or RCA, channel control via Rotary dial, source selector  Headphones output: 1 x stereo via Jack, channel control via Rotary dial
Housing design:	(19") 48.3 cm rack installation 4 U
Dimensions:	Width: 48,3 cm Depth: 11 cm Height: 17,8 cm
Weight:	3,70 kg