

OMNITRONIC LRS-1202ST Live Recording Mixer

Live recording mixer with 12 inputs

Art. No.: 10040226

GTIN: 4026397449136



Features:

- 2 mono input channels with gain control, 3-way EQ, low cut and pan control
- 4 stereo input channels with balance control
- Adjustable FX send output
- Inserts for the mono input channels
- Tape input and output
- Separate main mix and control room outputs
- Adjustable headphones output
- Master fader
- +48 V phantom power, can be switched centrally
- Precise 4-digit stereo LED level display
- Operation via supplied power unit

Logistic

EAN / GTIN: 4026397449136

Weight: 1,90 kg

Length: 0.33 m

Width: 0.24 m

Height: 0.10 m

Technical specifications:

Power consumption:	10.00 W
Frequency range:	20 - 20000 Hz
Dimensions:	Width: 22.5 cm Depth: 19 cm Height: 5 cm
Weight:	1.55 kg
Power supply:	2 x 18.5 V AC, 350 mA via supplied PSU

Inputs/sensitivity:

Mic, mono	0.5 mV, combined XLR/6.3 mm jack bal.
Insert	140 mV, 6.3 mm jack unbal.
Line In, stereo	38 mV/150 mV, 6.3 mm jack L/R bal.
Tape In	400 mV, RCA L/R

Outputs/level:

Main Out:	800 mV, 6.3 mm jack L/R unbal.
Control Room	max. 3 V, 6.3 mm jack L/R unbal.
FX Send	max. 10 V, 6.3 mm jack unbal.
Tape Out	60 mV, RCA L/R

Headphones	6.3 mm jack unbal.
------------	--------------------

Headphones impedance:	>8 ohms
-----------------------	---------

Distortion:	<0.04 %
-------------	---------

S/N ratio:	94 dB
------------	-------

Tone control/channel:

Treble:	±15 dB at 12 kHz
---------	------------------

Middle:	±15 dB at 2.5 kHz
---------	-------------------

Bass:	±15 dB at 80 Hz
-------	-----------------

Dimensions (W x D x H):	225 x 190 x 50 mm
-------------------------	-------------------

Scope of delivery:
