

OMNITRONIC MRS-1202USB Recording Mixer

Compact audio mixer with 12 inputs and USB interface

Art. No.: 10040272

GTIN: 4026397513899



The article is no longer in our assortment.

Features:

- Built-in USB audio interface allows recordings and playback of digital audio files with a computer (PC and Mac)
- Full duplex USB port: simultaneous recording and playback possible
- 2 mono input channels with gain control, 3-way EQ, Low Cut and pan control
- 4 stereo input channels with level switch and balance control
- Adjustable stereo aux send output
- Tape input and output
- Separate main mix and control room outputs
- Headphones output
- +48 V phantom power, can be switched centrally
- Precise 4-digit stereo LED level display
- Operation via supplied power unit
- Rugged, compact metal housing

Logistic

EAN / GTIN: 4026397513899
Weight: 2,58 kg
Length: 0.37 m
Width: 0.30 m
Height: 0.08 m

Technical specifications:

| | |
|--------------------|---|
| Power supply: | 230 V AC, 50 Hz |
| Power consumption: | 28,00 W |
| Power connection: | Mains input via Coaxial power connector (M) mounting version power supply cord with AC adapter (provided) |
| Frequency range: | 20 - 20000 Hz |
| S/N ratio: | >74 dB |

| | |
|-----------------------|---|
| USB port: | USB 2.0, Typ B |
| Dimensions: | Width: 35,5 cm Depth: 34,5 cm Height: 11,5 cm |
| Weight: | 2,35 kg |
| Inputs/sensitivity: | |
| Mic, mono | 0.5 mV, XLR bal. |
| Line In, mono | 0.5 mV, 6.3 mm jack bal. |
| Line In, stereo | 10 mV, 6.3 mm jack L/R |
| Tape In | 100 mV, RCA L/R |
| Outputs/level: | |
| Main Out: | 650 mV, 6.3 mm jack L/R unbal. |
| Control Room | 2 V max. 6.3 mm jack L/R unbal. |
| Aux Send: | 2 V, 6.3 mm jack unbal. |
| Tape Out | 2 V, RCA L/R |
| Headphones | 2 V, 6.3 mm jack unbal. |
| Distortion: | 0.05 % |
| Tone control/channel: | |
| Treble: | ±15 dB at 12 kHz |
| Middle: | ±15 dB at 2.5 kHz |
| Bass: | ±15 dB at 80 Hz |
| Phantom power: | +48 V |