

## OMNITRONIC CS-408 Powered Mixer

Universal powered stage mixer with 8 channels, 2 x 200 W/4 ohms

Art. No.: 10050050

GTIN: 4026397183283



### Features:

- Low-noise 8-channel mic/line mixer and amplifier with 2 x 200 W/4 ohms output power
- Adjustable digital reverb
- 8 mono input channels (XLR and 6.3 mm jack) with gain control, 2-band EQ, pan and effect control
- Insert or direct out (6.3 mm jack) per input channel
- Aux send per channel for controlling external effectors
- Adjustable effect way for controlling external effect units (aux send/return)
- Tape input and output, switchable (stereo RCA)
- Adjustable headphones output (6.3 mm jack)
- +48V phantom power, can be switched centrally
- 2 x 7-band graphic equalizer for fine-tuned sound
- Precise 5-fold stereo LED meter
- 2 Speaker outputs
- Digital signal processor

### Logistic

EAN / GTIN: 4026397183283

Weight: 11,10 kg

Length: 0.35 m

Width: 0.35 m

Height: 0.54 m

### Technical specifications:

Power supply: 115/230 V AC, 50/60 Hz

Power consumption: 800.00 W

Output power: Max. 400 W

200 W RMS (4 ohms)

|                       |  |
|-----------------------|--|
| Power connection:     | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Frequency range:      | 10 - 60000 Hz microphone<br>10 - 60000 Hz mono<br>10 - 55000 Hz stereo                           |
| S/N ratio:            | >112 dB  |
| THD:                  | <0.01 % at 1 kHz   |
| DSP:                  | Digital signal processor   |
| Circuitry:            | Class AB   |
| Equalizer:            | Master: 2 x graphic equalizer 7-band   |
| Dimensions:           | Width: 44 cm<br>Depth: 26 cm<br>Height: 27.5 cm  |
| Weight:               | 9.20 kg  |
| Inputs:               |  |
| 8 mono                | XLR or balanced 6.3 mm jacks   |
| 1 Aux Return:         | balanced 6.3 mm jack   |
| 1 Tape In             | stereo RCA   |
| Outputs:              |  |
| 1 Main Out:           | Speaker sockets  |
| 1 Headphones          | balanced 6.3 mm jack   |
| 1 Aux Send:           | balanced 6.3 mm jack   |
| 1 Tape Out            | RCA  |
| Tone control/channel: |  |
| Treble:               | ±15 dB at 12 kHz   |
| Middle:               | ±15 dB at 2.5 kHz  |
| Bass:                 | ±15 dB at 80 Hz  |
| Power output sine:    |  |
| Stereo 4 ohms         | 2 x 200 W  |

### Scope of delivery:

---