

OMNITRONIC CS-812 Powered Mixer

Universal powered stage mixer with DSP effects unit

Art. No.: 10050150

GTIN: 4026397230802



Features:

- Low-noise 8-channel mic/line mixer and amplifier with 2 x 350 W/4 ohms output power
- Integrated DSP effect unit with LED display 256 effects
- 8 mono input channels (XLR and 6.3 mm jack) with gain control, 3-band EQ, pan and effect control
- Insert or direct out (6.3 mm jack) per channel
- Aux send per channel for controlling external effectors
- Adjustable aux return input (6.3 mm jack)
- 2 adjustable CD inputs (stereo RCA) with crossfader
- Tape output (stereo RCA)
- +48V phantom power, can be switched centrally
- 2 x 7-band graphic equalizer for fine-tuned sound
- Precise 10-fold stereo LED meter
- 2 Speaker outputs

Logistic

EAN / GTIN: 4026397230802

Weight: 17,25 kg

Length: 0.42 m

Width: 0.42 m

Height: 0.64 m

Technical specifications:

Power supply: 115/230 V AC, 50/60 Hz

Power consumption: 1200.00 W

Output power: Max. 700 W

Dimensions: Width: 54 cm
Depth: 33 cm
Height: 32 cm

Weight:	14.00 kg
Inputs:	
8 mono	XLR or balanced 6.3 mm jacks
8 inserts	balanced 6.3 mm jacks
1 aux return	balanced 6.3 mm jacks
2 CD	RCA
Outputs:	
2 master	Speaker sockets
1 aux send	balanced 6.3 mm jacks
8 insert	balanced 6.3 mm jacks
1 Tape	RCA
Frequency range:	
Microphone:	10-60000 Hz, ± 3 dB
Mono:	10-60000 Hz, ± 3 dB
Stereo:	10-55000 Hz, ± 3 dB
Distortion:	0.01 %
S/N-ratio:	112 dB
Tone control/channel:	
Treble:	± 15 dB at 12 kHz
Middle:	± 15 dB at 2.5 kHz
Bass:	± 15 dB at 80 Hz
Power output sine:	
Stereo 4 ohms:	2 x 350 W
Dimensions (W x D x H):	540 x 330 x 320 mm

Scope of delivery:
