

## OMNITRONIC CFL-3242 Live Mixer

32-channel live mixer

Art. No.: 10060375

GTIN: 4026397304732



### Description:

Something for everybody. The smallest unit of this CFL live mixer series disposes of 12, the biggest unit disposes of 32 mono inputs. Normally, live mixers have faders from 70 - 80 mm. The CFL series has remarkably long faders that easily reach 100 mm. Although it is very low-priced, the series is highly resistant and by offering four subgroups and four Aux-Sends it is really well equipped. In total: powerful but not pricy.

### Features:

- 32 mono inputs with XLR sockets and balanced line inputs
- +48V phantom power per channel
- 2 stereo inputs via balanced jacks
- 2 stereo effect returns
- Insert for every mono channel
- High pass filter and 3-band EQ with semi-parametric mids for all mono inputs
- 4 groups for levelling complete signal groups (e.g. drums)
- Mutes for every channel
- 4 aux send (2 pre, 2 post) per channel for controlling the effects and for monitoring
- Separate master, group, monitor outputs
- 100 mm faders
- Precise 12-digit LED meter in subgroups and stereo master

### Logistic

EAN / GTIN: 4026397304732

Weight: 28,10 kg

Length: 1.32 m

Width: 0.26 m

Height: 0.67 m

Bulky product

### Technical specifications:

Power supply: 115/230 V AC, 50/60 Hz

|                         |                                                |
|-------------------------|------------------------------------------------|
| Power consumption:      | 100.00 W                                       |
| Dimensions:             | Width: 129 cm<br>Depth: 53 cm<br>Height: 16 cm |
| Weight:                 | 23.85 kg                                       |
| Inputs:                 |                                                |
| 32 mono                 | XLR or balanced 6.3 mm jacks                   |
| 32 inserts              | 6.3 mm jacks                                   |
| 2 stereo                | 6.3 mm jacks                                   |
| 4 Aux-Return            | balanced 6.3 mm jacks                          |
| Outputs:                |                                                |
| 2 Main Out:             | XLR or balanced 6.3 mm jacks                   |
| 1 Monitor               | balanced 6.3 mm jack                           |
| 4 Group Out             | 6.3 mm jack                                    |
| 4 Aux Send:             | balanced 6.3 mm jack                           |
| Rec Out                 | RCA                                            |
| Frequency range:        | 10-60000 Hz, ±3 dB                             |
| Dimensions (W x D x H): | 1290 x 530 x 160 mm                            |

**Scope of delivery:**