

OMNITRONIC ZD-250 Zone Distributor

Practical distributor with 2 inputs and 5 outputs







List price: 296.31 €

incl. 19% VAT.

Features:

- Extends every mixer with additional outputs
- 2 stereo XLR inputs
- 5 stereo zone XLR outputs
- Each zone with level controls for both inputs and mono switch
- LED display of signal input, distortion and mono/stereo mode
- (19") 48.3 cm rack installation 1 U
- For application areas such as: Installation; restaurants, bars and hotels; sports centres/gyms Package contents
- 1 x device, 1 x power cord, 1 x user manual

Technical specifications:

Power supply:	115/230 V AC, 50/60 Hz
Power consumption:	7,00 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
S/N ratio:	>69 dB
THD:	<0,2 % at 1 kHz
Impedance:	Input: 45,1 kOhm Output: 125 Ohm
Gain:	15 dB

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Logistic

EAN / GTIN: 4026397179125 Weight: 2,75 kg Length: 0.54 m Width: 0.27 m Heigth: 0.09 m

Max. level:	Input: +9 dB Output: +22 dB
Color:	Silver
Housing design:	(19") 48.3 cm rack installation 1 U
Dimensions:	Width: 48,3 cm
	Depth: 12,6 cm
	Height: 4,45 cm
Weight:	2,35 kg