

OMNITRONIC DYN-220 Compressor/Limiter

2-channel compressor/limiter with noise gate

Art. No.: 10355591

GTIN: 4026397522846



The article is no longer in our assortment.

Features:

- Threshold, ratio and output level control per channel
- Variable gate with threshold control per channel
- Bypass switch allows instant comparison of original sound with processed sound
- Precise 4-digit LED gain reduction meters
- +4 dB/-10 dB selector switch for internal level adjustment
- Inputs and outputs via balanced XLR connectors and 6.3 mm jacks
- (19") 48.3 cm rack installation 1 U

Logistic

EAN / GTIN: 4026397522846

Weight: 2,28 kg

Length: 0.54 m

Width: 0.20 m

Height: 0.10 m

Technical specifications:

| | |
|--------------------|--|
| Power supply: | 230 V AC, 50 Hz |
| Power consumption: | 20 W |
| Power connection: | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Frequency range: | 20 - 20000 Hz |
| S/N ratio: | >90 dB |
| THD: | <0,05 % at 1 kHz |
| Impedance: | Input: 20 kOhm , bal. Input: 10 kOhm , unbal. Output: 300 Ohm , unbal. |

| | |
|-----------------|--|
| | Output: 150 Ohm , bal. |
| Parameter: | Gate threshold: -80 to +20 dBU, arbitrary Compressor threshold: -40 to +20 dBU, arbitrary Compressor ratio: to 1:1 bis ∞:1, arbitrary |
| Crosstalk: | >80 dB |
| Status LED: | Gain-reduction-VU-meter |
| Connections: | Input: line via 2 x 3-pin XLR Input: line via 2 x 6.3 mm jack socket (mono) mounting version Output: line via 2 x 3-pin XLR Output: line via 2 x 6.3 mm jack socket (mono) mounting version |
| Housing design: | (19") 48.3 cm rack installation 1 U |
| Dimensions: | Width: 48,3 cm Depth: 15,4 cm Height: 4,45 cm |
| Weight: | 1,91 kg |