

## **OMNITRONIC TRM-202MK2 2-Channel Rotary Mixer**

2-channel rotary mixer with 3-band frequency isolator for DJs

Art. No.: 10355921 GTIN: 4026397541816











# The article is no longer in our assortment.

#### Features:

- Classic rotary mixer with 2 input channels and integrated 3-band frequency isolator for DJs
- Gain control, 2-way equalizer (Highs/Lows) and phono/line switching per channel
- Dedicated boost and kill cut
- Kill cut feature allows DJs to completely remove low, mid and high frequencies for amazing mixing
- Vintage ALPS potentiometers (Blue Velvet RK27)
- High-grade components ensure long life and excellent sound quality
- DJ microphone input with separate level control
- Prefader listening to input channels and the master output via adjustable headphones output, with cue mix/split function
- 10-digit stereo LED level meter and master level control
- Booth output with separate level control
- Inputs: 4 x line and 2 x phono (RCA L/R), DJ microphone (XLR) and headphones (jack)
- Outputs: master and booth (XLR/RCA L/R), record (stereo RCA)
- Operation via supplied power unit

#### **Technical specifications:**

Dimensions:	Width: 23,5 cm
	Depth: 19 cm
	Height: 9,5 cm
Weight:	2,87 kg
Power supply:	100-240 V AC, 50/60 Hz

### Logistic

EAN / GTIN: 4026397541816

Weight: 3,54 kg Length: 0.45 m Width: 0.24 m Heigth: 0.14 m

1/12	CIID	nlıad	power	LIDI
via	SUD	DIICU	DOWEI	ulli

Power consumption:	10 W	
Gain:		
Line:	20 dB	
Phono:	60-75 dB	
Mic:	44 dB	
Max. output level:	22 dBu	
Frequency range:		
Line:	20-20000 Hz	
Phono:	40-18000 Hz	
Mic:	20-20000 Hz	
S/R ratio:		
Line:	85 dB	
Phono:	77 dB	
Mic:	80 dB	
THD:		
Line:	<0.03 %	
Phono:	<0.1 %	
Frequency isolator:		
Lows:	20 Hz to 300 Hz	
Mids:	300 Hz to 4 kHz	
Highs:	4 kHz to 20 kHz	
Inputs:		
LINE:	RCA L/R	
PHONO:	RCA L/R	
DJ microphone:	XLR	
Outputs:		
MASTER:	XLR/RCA L/R	
BOOTH:	XLR/RCA L/R	
REC:	RCA L/R	
Headphones output:	6.3 mm jack (min. 32 ohms)	
Dimensions (W x D x H):	235 x 190 x 95 mm	