

OMNITRONIC TRM-202MK3 2-Channel Rotary Mixer (25th Omnitronic anniversary edition)

2-channel rotary mixer with 3-band frequency isolator for DJs

GTIN: 4026397691634



Features:

- Classic rotary mixer with 2 input channels and integrated 3-band frequency isolator for DJs
- Gain control, 2-way equalizer (highs/low) and phono/line switching per channel
- Dedicated boost and kill cut
- Kill cut feature allows DJs to completely remove low, mid and high frequencies for amazing mixing
- Vintage ALPS potentiometers (Blue Velvet RK27)
- High-grade components ensure long life and excellent sound quality
- DJ microphone input with separate level control
- Prefader listening to input channels and the master output via adjustable headphones output, with cue mix/split function
- 12-digit stereo LED level meter and master level control
- Booth output with separate level control
- Inputs: 4 x line and 2 x phono (RCA L/R), DJ microphone (XLR) and headphones (jack)
- Outputs: master and booth (XLR/RCA L/R), record (stereo RCA)
- Matching woodkits available at www.omniwoodkit.com
- Desktop console housing

Logistic

EAN / GTIN: 4026397691634

Weight: 3,18 kg

Length: 0.14 m

Width: 0.25 m

Height: 0.32 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 20 W

Protection class: Protection class I

| | |
|-------------------|--|
| Power connection: | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Frequency range: | 20 - 20000 Hz microphone 20 - 20000 Hz line 40 - 18000 Hz phono |
| S/N ratio: | >77 dB phono >80 dB microphone >85 dB line |
| THD: | Line <0.03 % at 1 kHz Phono <0.1 % at 1 kHz |
| Gain: | Microphone 44 dB Line 20 dB Phono 60 dB to +75 dB |
| Isolators: | Master Gain: - ? bis +9 Low/mid 300 Hz, 18db/oct , Butterworth Mid/high 4000 Hz, 18db/oct , Butterworth |
| Control elements: | Power switch, source selector |
| Status LED: | Power, master level meter, channel source, CUE, microphone |
| Connections: | Input: line via 2 x stereo RCA Input: line/phono via 2 x stereo RCA Input: microphone via 1 x 3-pin XLR Output: headphones via 1 x 6.3 mm jack socket (stereo) mounting version Output: rec. via 1 x stereo RCA Output: booth via 2 x 3-pin XLR Output: booth via 1 x stereo RCA Output: master via 2 x 3-pin XLR Output: master via 1 x stereo RCA |
| Channels: | Input channel: 2 x stereo with line-line/phono switch via RCA, channel control via rotary, 2-band tone control EQ, phono gain rotary, source selector, CUE switch Microphone channel: 1 x mono via XLR, channel control via rotary dial Booth output: 1 x stereo via XLR or RCA, channel control via rotary dial Master output: 1 x stereo via XLR or RCA, channel control via rotary dial Headphones output: 1 x stereo via jack, channel control via rotary dial |
| Max. level: | Output: +22 dBu |
| Housing design: | Desktop console housing |
| Dimensions: | Width: 19 cm Depth: 25 cm Height: 10.7 cm |
| Weight: | 2.68 kg |

Scope of delivery: