

## OMNITRONIC XPA-350 MK2 Amplifier

Class AB PA amplifier with limiter, 2 x 175 W RMS (4 ohms), 2 x 130 W RMS (8 ohms)

Art. No.: 10451001

GTIN: 4026397730760



**List price: 236.81 €**

incl. 19% VAT.

### Features:

- 2 level controls
- Signal inputs via XLR or RCA connectors
- Speaker outputs via lockable speaker jacks and pairs of screw terminals
- Class AB circuitry
- Highly efficient Air flow from front to rear
- The device is cooled by temperature-controlled fan
- (19") 48.3 cm rack installation 2 U
- For application areas such as: Clubs/dancing school; Installation; mobile use; mobile djs / entertainer; restaurants, bars and hotels; Rental; sports centres/gyms; Band/rehearsal room

#### Package contents

- 1 x amplifier, 1 x power cord, 4 x foot, 1 x user manual

### Logistic

EAN / GTIN: 4026397730760

Weight: 8,75 kg

Length: 0.55 m

Width: 0.43 m

Height: 0.14 m

### Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	245 W 1/8 power
Protection class:	Protection class I
Output power:	2 x 175 W RMS (4 ohms) 2 x 130 W RMS (8 ohms) 350 W RMS bridged (8 ohms)

Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Cable length:	1 m detachable
Fuse:	5 x 20 mm, F 8 A Fuse serviceable
Frequency range:	20 - 20000 Hz
S/N ratio:	>95 dB
THD:	<0,5 % at 1 kHz
Cooling:	1 x temperature-controlled fan , Air flow from front to rear
Impedance:	Input: 20 kOhm , bal. Input: 10 kOhm , unbal.
Gain:	30 dB/ 1 V
Housing color:	Black
Circuitry:	Class AB
Slew rate:	>20 V/ $\mu$ s
Damping factor:	>200
Control elements:	Power switch, level control per channel, mode switch (stereo/parallel/bridged)
Controls:	Short-circuit; overheat; DC voltage; softstart; power on/off transients; VHF; current limiting; limiter
Status LED:	Power, signal, clip, protect
Connections:	Input: line via 2 x 3-pin XLR Input: line via 2 x stereo RCA Output: speaker via 2 x speaker built-in socket (F) Output: speaker via screw terminal Output: Speaker (bridge) via 1 x speaker built-in socket (F) Output: Speaker (bridge) via screw terminal
Input sensitivity:	1 V
Housing design:	(19") 48.3 cm rack installation 2 U
Dimensions:	Width: 48,3 cm Depth: 36,8 cm Height: 9,1 cm
Weight:	7,65 kg