

OMNITRONIC XPA-3004 Amplifier

4-channel PA amplifier with integrated limiter, 4 x 750 W / 4 ohms, 4 x 500 W / 8 ohms

Art. No.: 10451038

GTIN: 4026397594959



List price: 712.81 €

incl. 19% VAT.

Features:

- 3 operating modes can be selected (stereo, parallel or bridged)
- Input sensitivity adjustable
- Level control per channel
- Each channel with LED for activated protective circuit (protect) and output meter with clip LED
- Signal inputs via XLR connectors
- Speaker outputs via lockable Speaker plugs
- Class H circuitry
- Highly efficient Air flow from front to rear
- The device is cooled by temperature-controlled fan
- (19") 48.3 cm rack installation 2 U

Package contents

- 1 x amplifier, 1 x user manual, 4 x foot, 4 x screw, 1 x power cord

Logistic

EAN / GTIN: 4026397594959

Weight: 20,60 kg

Length: 0.55 m

Width: 0.53 m

Height: 0.14 m

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	700 W 1/8 power
Output power:	4 x 750 W RMS (4 ohms) 4 x 500 W RMS (8 ohms) 2 x 1500 W RMS bridged (8 ohms)
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)

Frequency range:	20 - 20000 Hz
S/N ratio:	>100 dB
THD:	<0,5 % at 1 kHz
Cooling:	2 x temperature-controlled fan , Air flow from front to rear
Impedance:	Input: 20 kOhm , bal. Input: 10 kOhm , unbal.
Circuitry:	Class H
Slew rate:	>10 V/μs
Damping factor:	>200
Control elements:	Power switch, level control per channel, mode switch (stereo/parallel/bridged), Input sensitivity switch
Controls:	Short-circuit; overheat; DC voltage; power on/off transients; softstart; power on/off transient
Status LED:	Power, level meter, clip, bridged, protect
Connections:	Input: line via 4 x 3-pin XLR Output: speaker via 4 x speaker built-in socket (F) Output: Speaker (bridge) via 2 x speaker built-in socket (F)
Input sensitivity:	0,775 V; 1,4 V , switchable
Housing design:	(19") 48.3 cm rack installation 2 U
Dimensions:	Width: 48,3 cm Depth: 41,5 cm Height: 8,9 cm
Weight:	19,20 kg