

OMNITRONIC P-3500 Amplifier, 2x1040W/8ohm

Very powerful PA amplifier

Art. No.: 10451195 GTIN: 4026397241907





The article is no longer in our assortment.

Features:

- 2 operating modes can be selected (stereo or bridged)
- 2 x 1040 W/8 ohms
- Enormous power with highest brilliance
- 2 gain controls on the front panel
- All operation modes controllable via LEDs
- LED intensity adjustable via brightness control on the rear panel
- Signal inputs via XLR female or 6.3 mm jack socket
- Input sensitivity adjustable via selector on the rear panel
- Speaker connection via lockable Speaker plugs or Banana/screw combination
- With limiter
- Ground Lift switch against humming
- Bridged switch for bridging
- Many protection circuits for optimized equipment protection
- Very rugged housing
- Rack installation
- High power/weight-relation

Technical specifications:

Power supply:	115/230 V AC, 50/60 Hz
Power consumption:	4500,00 W
Output power:	1040 W RMS (8 ohms)
Dimensions:	Width: 48.3 cm

Logistic

EAN / GTIN: 4026397241907

Weight: 25,00 kg Length: 0.52 m Width: 0.52 m Heigth: 0.18 m

	Depth: 44 cm
	Height: 8,9 cm
Weight:	24 kg
Power range:	230 V ±10 % (207-253 V)
Power output sine:	
Stereo 8 ohms	2 x 1040 W
8 ohms bridged	1 x 3300 W
Frequency range:	10-50000 Hz, ±1.5 dB
Damping factor:	>150
Distortion factor:	0.01 %
Signal-to-noise ratio:	90 dB
Channel seperation (at 1 kHz):	70 dB
Min. input sensitivity:	0.77 V/26 dB/1.4 V
Input impedance:	20 kohms (balanced)
Slew rate:	60 V/µsec
Input connectors:	2 x XLR female plug, 2 x 6.3 mm jack plug
Output connectors:	2 x Speaker (stereo), 1 x Speaker (bridge), 2 x Banana/screw combination
Control elements:	Power switch, input attenuators (one per channel), Mode switch - Stereo/Parallel/Bridged, Ground Lift, Input-Level-Select (0.77 V/26 dB/1.44 V), limiter
LED indicators (per channel):	Power, Protect, Signal, Mode

460 m

Short-circuit, DC,tThermal, softstart

Steel chassis, aluminum front panel

Protection circuits:

Minimum mounting depth:

Construction: