

**PSSO**<sup>®</sup>

---

## HSP-4000 MK2 SMPS Amplifier

Class H stereo PA amplifier with SMPS, 2 x 1200 W RMS (8 ohms), 2 x 2000 W RMS (4 ohms)

**Art. No.: 10451694**  
GTIN: 4026397505924



**The article is no longer in our assortment.**

---

All rights reserved. Subject to change without notice. Errors and omissions excepted.  
Illustration only. Actual item may differ from photo.

**PSSO**<sup>®</sup>

---

## HSP-4000 MK2 SMPS Amplifier

Class H stereo PA amplifier with SMPS, 2 x 1200 W RMS (8 ohms), 2 x 2000 W RMS (4 ohms)

**Art. No.: 10451694**  
GTIN: 4026397505924

### Features:

---

- Stereo PA amplifier with class H circuitry
- Low weight and height due to integrated switch mode power supply
- Reliable power amp with high impulse stability for a wide range of applications (e.g. compact PAs, multi-way PAs, international concerts)
- Limiter and speaker switch-on delay
- 3 operating modes can be selected (stereo, parallel or bridged)
- 2 calibrated level controls for precise level adjustment
- Input sensitivity and limiter adjustable
- LED VU meter and LEDs for activated protective circuit (protect), overload (clip), and signal per channel
- LEDs for parallel and bridge mode
- Complete protection set against short-circuit, overheat, clipping, overload, DC voltage and VHF signals
- Highly efficient front-to-rear air routing
- Electronically balanced inputs via XLR mounting jacks, with XLR feed-through outputs
- Speaker outputs via lockable Speaker plugs and screw terminals

---

All rights reserved. Subject to change without notice. Errors and omissions excepted.  
Illustration only. Actual item may differ from photo.