

OMNITRONIC C-80A active black 2x

Active 2-way speaker pair with mount, 8" woofers and 80 W RMS

Art. No.: 11036724

GTIN: 4026397356410



Features:

- Dedicated PA speaker system for fixed installations
- 2-way bass-reflex system for powerful bass
- 20 cm woofer (8") and 2.5 cm dome tweeter (1")
- 2-way tone control and level control
- Signal input and output via balanced XLR connectors
- White or titanium plastic housing (ABS) with metal grille
- Trapezoidal cabinet for corner installation
- Movable mounting bracket for ceiling or wall installation
- Ideal for PA applications in restaurants, bars, discos, shops, conferences, etc.
- With mounting bracket

Logistic

EAN / GTIN: 4026397356410

Weight: 17,45 kg

Length: 0.58 m

Width: 0.32 m

Height: 0.43 m

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	125 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power:	Program: 125W Rated: 80W RMS
Frequency range:	50 - 20000 Hz
Sensitivity:	90 dB (1W/1m)

Attachment system:	Mounting bracket
Connections:	Input: line via 2 x 3-pin XLR
Speaker:	1 x woofer 8"
Color:	Black
Dimensions:	Width: 27 cm Depth: 24 cm Height: 36 cm
Weight:	15.55 kg
Components:	20 cm woofer (8"), 2.5 cm tweeter (1")
Input:	3-pin XLR
Output:	3-pin XLR
Sensitivity:	90 dB
Dimensions (H x W x D):	360 x 270 x 240 mm

Scope of delivery:
