

OMNITRONIC OD-22 Wall Speaker 80hms black

Weather-proof 2,5" wall speaker (IP44) with mount, 20 W RMS

Art. No.: 11036906 GTIN: 4026397543506







List price: 43.91 €

incl. 19% VAT.

Features:

- 8-ohm PA speaker system for general applications
- 2 x 6 cm full-range speaker (2 x 2.5")
- 3.5 x 6 cm passive membrane
- Durable mounting plate with joint for panning and tilting allows ceiling or wall installation in most varying angles
- With panning and tilting mounting bracket for ceiling or wall installation in most varying angles
- Black aluminum grille
- Scratchproof and shockproof
- Suitable for outdoor use IP44
- For application areas such as: Trade fair and shop fitting; restaurants, bars and hotels; product presentations and lectures

Package contents

- 1 x compact cabinet speaker, 1 x user manual, 1 x mounting material, 8 x screw

Technical specifications:

IP classification:	IP44
Power:	Program: 40W Rated: 20W RMS
Frequency range:	120 - 22000 Hz
Sensitivity:	88 dB
Max. SPL:	104 dB

Logistic

EAN / GTIN: 4026397543506

Weight: 1,07 kg Length: 0.28 m Width: 0.14 m Heigth: 0.12 m

Dispersion angle:	60° x 60°
Impedance:	8 ohms
Attachment system:	Panning and tilting mounting bracket for ceiling or wall installation in most varying angles
Connections:	Speaker via Spring terminal
Speaker:	2 x full rage loudspeaker 2,5" Basket material: Steel
	Conematerial: Cardboard/paper
Material:	ABS Acrylonitrile butadiene styrene
Color:	Black, scratchproof and shockproof
Dimensions:	Width: 20,9 cm
	Depth: 10,9 cm
	Height: 11 cm
Weight:	930 g