

OMNITRONIC OD-5T Wall Speaker 100V black 2x

Weather-proof wall speaker pair (IP65) with 5.25" woofers and 40 W RMS

Art. No.: 11036920

GTIN: 4026397543605



Description:

Weatherproof wall speaker pair

The weatherproof pair of OD-5T wall speakers has an excellent sound image and is ideal for your indoor and outdoor use.

The 2-way system is equipped with a 13.5 cm woofer, a 1.5 cm tweeter and a 100 V transformer with 4 power taps.

The sound reinforcement speakers in weatherproof (IP65) plastic housing have a tilt and swivel mounting bracket for easy wall and ceiling mounting at any angle.

Features:

- 2-way system with 13.5 cm woofer (5.25") and 1.3 cm tweeter (0.5")
- Durable plastic cabinet with metal grille and cover for the connectors
- Power selector switch with 8 ohms operating position
- With panning and tilting mounting bracket for ceiling or wall installation in most varying angles
- Black aluminum grille
- Suitable for outdoor use IP65
- 2 pieces per set
- For application areas such as: Trade fair and shop fitting; restaurants, bars and hotels; product presentations and lectures

Logistic

EAN / GTIN: 4026397543605

Weight: 5,65 kg

Length: 0.42 m

Width: 0.20 m

Height: 0.28 m

Technical specifications:

IP classification:	IP65
Power:	Program: 80W Rated: 40W RMS (8 ohms) Rated: 16W RMS (100V PA)
Frequency range:	80 - 20000 Hz
Sensitivity:	89 dB
Max. SPL:	101 dB (100V PA); 108 dB (8 ohms)
Dispersion angle:	170° x 170°
Impedance:	Public address systems 100V; 8 ohms
Attachment system:	Panning and tilting mounting bracket for ceiling or wall installation in most varying angles
Power tapping:	2W; 4W; 8W; 16W RMS via selector switch switchable
Control elements:	Level control
Connections:	Input: speaker via screw terminal
Speaker:	Woofer 5.25" Basket material: steel Dome tweeter 0.5"
Type of speaker:	Compact cabinet speaker
Material:	Plastic
Color:	Black
Dimensions:	Width: 16 cm Depth: 16.3 cm Height: 25.5 cm
Weight:	5.30 kg

Scope of delivery:

2 x compact cabinet speaker
2 x mounting bracket
4 x knurled screw
1 x user manual