

OMNITRONIC OD-6A Wall Speaker active black 2x

Active 2-way speaker pair with mount, 6,5" woofers and 45 W RMS

Art. No.: 11036928 GTIN: 4026397543681









The article is no longer in our assortment.

Features:

- Dedicated PA speaker systems for fixed installations
- 2-way system with 16.5 cm woofer (6.5") and dome tweeter, magnetic shielding
- Class A/B circuitry: optimum sound and power at low weight and compact dimensions
- Separate controls for volume, high and low frequencies
- Each speaker system is equipped with an unbalanced RCA input and balanced spring terminals
- Additional 3.5 mm jack input, ideal for portable MP3 players
- Attractive plastic cabinet with metal grille
- Panning and tilting mounting bracket allows ceiling or wall installation in most varying angles
- Packed as a pair
- For indoor PA applications
- With panning and tilting mounting bracket for ceiling or wall installation in most varying angles

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with Euro plug (provided)
Power:	Program: 90W
	Rated: 45W RMS
Frequency range:	80 - 20000 Hz
Sensitivity:	89 dB

Logistic

EAN / GTIN: 4026397543681 Weight: 9,50 kg Length: 0.50 m Width: 0.23 m Heigth: 0.33 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Max. SPL:	96 dB
Dispersion angle:	170° x 170°
Attachment system:	Panning and tilting mounting bracket for ceiling or wall installation in most varying angles
Circuitry:	Class AB
Connections:	Line via 1 x 3.5 mm jack (mono) mounting version Line via 1 x RCA (F) mounting version
Speaker:	1 x woofer 6,5" 1 x horn 1"
Color:	Black
Dimensions:	Width: 19,5 cm Depth: 19,5 cm Height: 30 cm
Weight:	8,90 kg