OMNITRONIC ODP-204 Installation Speaker 16 ohms white 2x

2 weather-proof 4" wall speakers (IP65) with mount, 40 W RMS

Art. No.: 11036951

GTIN: 4026397629699

List price: 189.21 €

incl. 19% VAT.

Description:

Great sound - also runs with 100 volts
You want reliable and balanced sound for your bar, restaurant, shop or the conference area of your hotel? You need indoor and outdoor speakers? With the OPD series you get powerful installation speakers that meets all your requirements.

The speakers have a brilliant sound pattern and are available in a low ohm (16 ohms) and in a 100 V version. These two cover both small and large installations. A rotatable mounting bracket is included in the delivery. A swivel wall mount with matching colors is optionally available.

With their weatherproofed (IP65) plastic cabinet the ODP speakers are well prepared for outdoor use, indoor use is of course also possible.

Features:

- 16-ohm PA speaker systems with an excellent sound for general applications
- 2-way system with 10 cm woofer (4") and 2 cm dome tweeter (0.8")
- Durable plastic cabinet with metal grille
- Screw plug terminal for easy handling
- With Mounting bracket
- Suitable for outdoor use IP65
- 2 pieces per set
- For application areas such as: Trade fair and shop fitting; restaurants, bars and hotels; product presentations and lectures

Package contents

- 1 x user manual, 1 x top, 1 x mounting bracket, 6 x screw, 1 x safety eyelet, 1 x lid, 4 x washer, 2 x screwing

Logistic

EAN / GTIN: 4026397629699
Weight: 5,75 kg
Length: 0.41 m
Width: 0.19 m
Heigth: 0.30 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Technical specifications:

IP classification:	IP65
Power:	Program: 80W Rated: 40W RMS (16 Ohm)
Frequency range:	75 - 20000 Hz
Sensitivity:	88 dB (1W/1m)
Max. SPL:	103 dB
Dispersion angle:	120° x 90°
Impedance:	16 ohms
Attachment system:	Mounting bracket
Connections:	Speaker via screw terminal
Crossover frequency:	3500 Hz
Speaker:	1 x woofer 4" Voice coil lows 1" 1 x Calottes highs 0,8" Voice coil calotte tweeter 0,8"
Type of speaker:	Compact cabinet speaker; On-ceiling/on-wall speaker
Color:	White
Dimensions:	Width: 14,1 cm Depth: 17 cm Height: 23 cm
Weight:	5,10 kg

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.