



Features:

- Ideal bass support of ODX full-range speakers
- Durable plastic cabinet with metal grille
- Power selector switch with 8 ohms operating position
- Screw terminals for parallel connection
- With mounting bracket
- Suitable for outdoor use IP56
- For application areas such as: Installation; sports centres/gyms; multi-purpose hall

Logistic

EAN / GTIN: 4026397708929
Weight: 28,40 kg
Length: 0.61 m
Width: 0.59 m
Heigh: 0.57 m

Technical specifications:

IP classification:	IP56
Power:	Program: 800W Rated: 400W RMS
Frequency range:	45 - 300 Hz
Sensitivity:	98 dB
Max. SPL:	130 dB
Dispersion angle:	Omnidirectional
Impedance:	8 ohms; public address systems 100V
Attachment system:	Mounting bracket
Power tapping:	75W; 150W; 300W RMS via selector switch switchable

Connections:	Input: speaker via screw terminal
Speaker:	1 x woofer 15" Voice coil lows 3"
Type of speaker:	Subwoofer
Type of construction:	Vented
Color:	Light gray
Dimensions:	Width: 49 cm Depth: 52 cm Height: 50 cm
Weight:	24.80 kg

Scope of delivery:

- 1 x mounting bracket
- 1 x user manual
- 6 x screw
- 1 x safety eyelet
- 1 x lid
- 8 x washer
- 1 x bass
- 1 x screwing