

OMNITRONIC ODX-115ST Installation Subwoofer 100V white

Weather-proof 15" wall subwoofer with mount, 400 W RMS

Art. No.: 11036970 GTIN: 4026397708929











List price: 784.21 €

incl. 19% VAT.

Features:

- Ideal bass support of ODX full-range speakers
- Durable plastic cabinet with metal grille
- Power selector switch with 8 ohms operating position
- Screw terminals for parallel connection
- With mounting bracket
- Suitable for outdoor use IP56
- For application areas such as: Installation; sports centres/gyms; multi-purpose hall Package contents
- 1 x mounting bracket, 1 x user manual, 6 x screw, 1 x safety eyelet, 1 x lid, 8 x washer, 1 x bass, 1 x screwing

Technical specifications:

IP classification:	IP56
Power:	Program: 800W Rated: 400W RMS
Frequency range:	45 - 300 Hz
Sensitivity:	98 dB
Max. SPL:	130 dB
Dispersion angle:	Omnidirectional
Impedance:	8 ohms; public address systems 100V

Logistic

EAN / GTIN: 4026397708929 Weight: 28,40 kg Length: 0.61 m Width: 0.59 m Heigth: 0.57 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Attachment system:	Mounting bracket
Power tapping:	75W; 150W; 300W RMS via selector switch switchable
Connections:	Input: speaker via screw terminal
Speaker:	1 x woofer 15" Voice coil lows 3"
Type of speaker:	Subwoofer
Type of construction:	Vented
Color:	White
Dimensions:	Width: 49 cm Depth: 52 cm Height: 50 cm
Weight:	24,80 kg