

OMNITRONIC ODC-244T Outdoor Column Speaker white

Weather-proof column speaker in aluminium cabinet (4 x 4"), with mount, 130 W RMS

Art. No.: 11036978 GTIN: 4026397718195





List price: 474.81 €

incl. 19% VAT.

Features:

- Intelligible voice and superior sound reproduction
- 2-way system with 4 x 10 cm mid-woofer (4")
- Durable aluminum cabinet with grille
- Power selector switch with 8 ohms operating position
- With mounting bracket
- White aluminum grille with acoustic foam
- Suitable for outdoor use IP56
- For application areas such as: Installation; sports centres/gyms; multi-purpose hall Package contents
- 1 x top, 2 x angle, 1 x plug (male), 10 x washer, 4 x screw, 1 x user manual

Technical specifications:

IP classification:	IP56
Power:	Program: 260W
	Rated: 130W RMS (8 ohms)
	Rated: 120W RMS (100V PA)
Frequency range:	120 - 18000 Hz
Sensitivity:	94 dB (1W/1m)
Max. SPL:	121 dB
Dispersion angle:	100° x 50°

Logistic

EAN / GTIN: 4026397718195 Weight: 11,50 kg Length: 0.79 m Width: 0.23 m Heigth: 0.20 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Impedance:	8 ohms; public address systems 100V
Attachment system:	Mounting bracket
Power tapping:	30W; 60W; 120W RMS via selector switch switchable
Connections:	2-pin screw plug connector (M) mounting version IP
Crossover frequency:	1900 Hz
Speaker:	4 x woofer 4" with ferrit magnet Basket material: aluminum Voice coil lows 1" Diaphragmmaterial: mylar 1 x compression tweeter highs 1" with ferrit magnet Voice coil compression tweeter highs 1,4"
Type of speaker:	Column speaker
Type of construction:	Closed Box
Material:	Aluminum
Color:	White
Dimensions:	Width: 12,7 cm Depth: 14,4 cm Height: 70,4 cm
Weight:	10,50 kg