

## OMNITRONIC KM-110A Active Stage Monitor, coaxial

Monitor, 10" woofer, 1,35" driver, LF: 150 W RMS, HF: 50 W RMS

Art. No.: 11038035

GTIN: 4026397529883



**List price: 343.91 €**

incl. 19% VAT.

### Features:

- Active 2-way coaxial stage monitor for live and playback applications
- Class D/AB biamp power amplifier
- 25 cm bass speaker (10") and 3.5 cm compression driver (1.35")
- Bassreflex cabinet provides deep bass and high SPL
- Low cut, volume control
- Black metal grille
- For application areas such as: Stage; Band/rehearsal room; mobile use

#### Package contents

- 1 x compact cabinet speaker, 1 x user manual, 1 x power cord

### Logistic

EAN / GTIN: 4026397529883

Weight: 15,85 kg

Length: 0.46 m

Width: 0.41 m

Height: 0.54 m

### Technical specifications:

|                    |  |
|--------------------|--|
| Power supply:      | 115/230 V AC, 50/60 Hz   |
| Power consumption: | 80 W 1/8 power   |
| Power connection:  | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Power:             | Program: 300W<br>Rated: 50W RMS HF<br>Rated: 150W RMS LF   |
| Frequency range:   | 60 - 20000 Hz  |
| Max. SPL:          | 121 dB   |

|                   |  |
|-------------------|--|
| Dispersion angle: | 80° x 80°  |
| Controls:         | Overload; limiter  |
| Connections:      | Input: line via 1 x 3-pin XLR/6.35mm jack (F)<br>combination socket (mounting version)<br>Output: line via 1 x 3-pin XLR |
| Input channels:   | 1 x mono via XLR or jack, channel control via<br>Rotary dial   |
| Speaker:          | 1 x woofer 10" with ferrit magnet<br>1 x Voice coil compression tweeter highs 1,35"                                      |
| Type of speaker:  | Compact cabinet speaker; Coaxial speaker; stage<br>monitor   |
| Material:         | MDF (Medium-density fiberboard)  |
| Color:            | Black, textured coating, painted   |
| Dimensions:       | Width: 48 cm<br>Depth: 30 cm<br>Height: 42 cm  |
| Weight:           | 14,30 kg   |