# OMNITRONIC XKB-210A 2-Way Speaker, active, Bluetooth

Active speaker with 10" woofer, 1,35" driver, HF: 75 W RMS, LF: 175 W RMS

**Art. No.: 11038794**

GTIN: 4026397628340

## List price: 308.21 €

incl. 19% VAT.

### Description:

The speaker systems of the XKB series are high-performance active speaker systems in light-weight and rugged plastic cabinets. They can be flexibly used for permanent installations and professional live applications. The 2-way speaker systems are designed as full-range bass-reflex systems with separate power amplifiers for the high-frequency range and the low-frequency range featuring inputs for microphones and line sources and parallel outputs for coupling with other active speakers. The DSP (digital signal processor) features convenient application presets for quick sound contouring (models XKB-212A and XKB-215). The built-in Bluetooth player allows for streaming music wirelessly from smartphones or tablets via Bluetooth. The speakers systems are protected through limiters and extensive protective circuits. The enclosure offers multiple setup options (use as a floor monitor, wall or stand mounting).

### Logistic

EAN / GTIN: 4026397628340
Weight: 12,45 kg
Length: 0.58 m
Width: 0.36 m
Heigth: 0.37 m

### Features:

- Class D biamp amplifier (LF 175 W, HF 75 W)
- 2-way bass-reflex enclosure with 25 cm woofer and 3.5 cm driver
- 1 mic/line combo input (XLR/jack) with level control
- 1 line input (XLR/RCA) with level control
- Master control with 2-band EQ
- Control via Bluetooth
- Black metal grille with acoustic foam
- 3 Rugged carrying handles
- Application possibility: Standing; monitoring; on stand
- For application areas such as: Party room; mobile use; mobile djs / entertainer; small rental

**Package contents**

- 1 x compact cabinet speaker, 1 x user manual, 1 x power cord, 1 x declaration of conformity

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

## Technical specifications:

| | |
|---|---|
| Power supply: | 230 V AC, 50 Hz |
| Power consumption: | 550 W |
| Protection class: | Protection class I |
| Power connection: | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Power: | Program: 350W<br>Rated: 75W RMS HF<br>Rated: 175W RMS LF |
| Frequency range: | 65 - 20000 Hz |
| Sensitivity: | 95 dB |
| Control: | Bluetooth |
| Bluetooth device name: | Omnitronic XKB |
| Attachment system: | Flange: Ø 35mm |
| Circuitry: | Class D Biamp |
| Control elements: | Power switch, Input sensitivity switch, level control per channel, connect, tone control |
| Controls: | Limiter |
| Status LED: | Power, signal, limit, pairing |
| Connections: | Output: line via 1 x 3-pin XLR<br>Input: line via 1 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version)<br>Input: line via 1 x stereo RCA<br>Input: line via 1 x 3-pin XLR |
| Input channels: | 1 x mono via XLR or RCA or bluetooth, channel control via Rotary dial<br>1 x mono with Mic-line switch via Combination socket (XLR/jack), channel control via Rotary dial |
| Equalizer: | Master: 1 x 2-band tone control |
| Speaker: | 1 x woofer 10" with ferrit magnet<br>Basket material: Steel<br>Conematerial: Cardboard/paper<br>Voice coil lows 1,5"<br>Voice coil compression tweeter highs 1,35" |
| Type of speaker: | Compact cabinet speaker |
| Carrying handle: | 3 pc/pcs |
| Material: | Plastic |
| Color: | Black |
| Dimensions: | Width: 31 cm<br>Depth: 32 cm<br>Height: 48 cm |
| Weight: | 11,15 kg |

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.