

## OMNITRONIC XKB-215A 2-Way Speaker, active, DSP

Active speaker with 15" woofer, 1,75" driver, HF: 60 W RMS, LF: 300 W RMS

Art. No.: 11038796

GTIN: 4026397606492



**List price: 415.31 €**

incl. 19% VAT.

### Features:

- Active 15/2 full range system for mobile live and DJ applications
- DSP-controlled biamp amplifier (LF class D, HF class A/B)
- 24-bit DSP with adjustable high-pass filter, parametric 3-band EQ and signal delay
- Built-in Bluetooth player for audio streaming from compatible Bluetooth devices such as smartphones, tablets and notebooks
- 2-way bass-reflex enclosure with 38 cm woofer and 4 cm titanium driver
- 2 mic/line inputs (XLR/6.3 mm jack) with separate level controls
- Control via Bluetooth
- LCD display
- Black metal grille with acoustic foam
- 3 Rugged carrying handles
- Application possibility: Standing; monitoring; on stand
- Digital signal processor
- DSP presets: LIVE; MUSIC; SPEECH; DJ; TRIPOD; MONITOR; WALL
- For application areas such as: Mobile djs / entertainer; mobile use; Rental; sports centres/gyms

#### Package contents

- 1 x top, 1 x user manual, 1 x power cord, 1 x declaration of conformity

### Logistic

EAN / GTIN: 4026397606492

Weight: 22,55 kg

Length: 0.52 m

Width: 0.43 m

Height: 0.77 m

### Technical specifications:

Power supply: 230 V AC, 50 Hz

Power consumption: Max. 800 W

|                       |  |
|-----------------------|--|
| Power connection:     | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Power:                | Program: 600W<br>Rated: 60W RMS HF<br>Rated: 300W RMS LF   |
| Frequency range:      | 50 - 20000 Hz  |
| Sensitivity:          | 96 dB  |
| Max. SPL:             | 121 dB   |
| DSP:                  | Digital signal processor   |
| DSP presets:          | LIVE; MUSIC; SPEECH; DJ; TRIPOD; MONITOR; WALL   |
| Control:              | Bluetooth  |
| Attachment system:    | Flange: Ø 35mm   |
| Circuitry:            | Class D Biamp  |
| Display type:         | LCD display  |
| Control elements:     | Encoder, Master control  |
| Controls:             | Limiter  |
| Status LED:           | Power, signal, limit   |
| Connections:          | Output: line via 1 x 3-pin XLR   |
| Input channels:       | 2 x mono with Mic-line switch via Combination socket (XLR/jack), channel control via Rotary dial |
| Equalizer:            | Master: 1 x 3-band tone control  |
| Speaker:              | 1 x woofer 15"<br>Voice coil compression tweeter highs 1,75"                                     |
| Type of speaker:      | Compact cabinet speaker  |
| Type of construction: | Vented   |
| Carrying handle:      | 3 pc/pcs   |
| Dimensions:           | Width: 37 cm<br>Depth: 45 cm<br>Height: 70 cm  |
| Weight:               | 20,95 kg   |